

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6379)

-----  
Set ¼ sec. post, from which  
A Laurel 4" dia., bears N.55°E., 12 lks. dist.  
A Laurel 4" dia., bears N.25°W., 24 lks. dist.

G.A. Barnhart, - Wit: Weber; Stubblefield - Dec. 1946 - C.S. File 40/19A

-----  
Set a 3/4" Iron rod, 30" long, 2747.25 ft. from the sec. corners and on a true line between them, from which  
A 12" Fir bears S.68°17'W., 22.7 ft.  
A 2" Fir bears S.81°58'E., 4.2 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-109

-----  
Found - 3/4" Iron rod at corner and both BTs as recorded.  
2" now 5" R.Fir S.82°E., 4.2 ft., shows good scribing.  
12" now down Fir, S.68°W., 22.7 ft., shows scar.  
Set brass cap alongside 3/4" I.R. mkd:  
County Surveyors Office  
T 29 S R 4 W  
¼ S 30 | S 29  
1963  
New BT - 12" Maple bears N.83°W., 5.3 ft. scribed ¼ S30 CSBT  
Corner is 20 ft. North of bottom of small E-W draw.

Fd. Ok by D. Edwards, March 2002 - M139-75