

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6380)

Set a post cor. of secs. 19, 20, 29 and 30, from which
A B.Oak 10" dia., bears S.40°E., 63 lks. dist.
A W.Oak 8" dia., bears N.60°E., 127 lks. dist.
A B.Oak 12" dia., bears N.25°W., 45 lks. dist.
A B.Oak 10" dia., bears S.60°W., 45 lks. dist.

N.E. Richardson, Deputy Co. Surveyor - Wit: E.S. Woodford - May 1945 (No record souce found)

Renewed from old BTs. Set iron spring and shackle for corner from which
A 30" Fir bears N.32°E., 5.8 ft.
A 20" Fir bears S.55°E., 32.4 ft.
An 18" Fir bears N.45°W., 27.4 ft.
A 20" Fir bears S.76°W., 18.9 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-106

Found - Spring with shackle at cor. and 1" I.P. alongside.
30" now 36" R.Fir N.32°E., 7.0 ft., not 5.8 ft., shows bark scribing.
20" now 24" R.Fir S.55°E., 32.4 ft., shows bark scribing.
18" now 18" Fir N.52°W., not N.45°W., 27.4 ft., shows bark scribing.
SW. BT now stump.
Fence corner at NE. bearing tree.
New BTs -10" R.Fir bears N.82°W., 7.2 ft. scribed S20 T29S R4W CS BT.
6" R.Fir bears S.19°W., 28.5 ft. scribed S30 CSBT
14" Laurel bears S.12°E., 37.5 ft. scribed S29 R4W CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July/Oct 1977 (DCSO records Vol. 39 Page(s) 15893)

The sec. cor. perpetuated and recorded by Richardson in 1945, and further perpetuated and recorded by Byron in 1963, monumented with an iron spring and shackle, firmly set flush with the surface of the ground, projecting 12" above ground, from which the remains of the original bearing trees:
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 19, 20, 29 and 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A root hole bears S.60°W., 45 lks. dist., with a down B.Oak alongside 18" dia., with scribe marks BT visible on opened blaze.
A decayed and burned Oak root crown, size indeterminate, bears S.40°E., 60 lks. dist., no marks visible.
and the remains of bearing trees mkd. by Richardson
A Fir 36" dia., bears N.34°E., 10 lks. dist., with scribe marks S20 CS BT visible on bark.
A Fir 16" dia., bears S.51°E., 50 lks. dist., with scribe marks S29 CS BT visible on bark.
A sawed Fir stump 18" dia., bears S.74½°W., 30 lks. dist. with scribe marks BT visible on bark.
and bearing trees mkd. by Byron
A Madrone 14" dia., bears S.12°E., 57 lks. dist., with scribe marks T29S R4W S29 BT visible on open double blaze.
A Fir 8" dia., bears S.19°W., 44 lks. dist., with healed blaze.
A Fir 10" dia., bears N.82°W., 12 lks. dist., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over inverted spring, with brass cap mkd:
T 29 S R 4 W
S 19 | S 20
S 30 | S 29
1969
Reset iron pipe alongside iron post.

Fd. and tied in BLM resurvey by Boyd W. Peterson, under Group #1394, surveyed Aug. 1987/Jan. 1988 - (DCSO records, Vol. 48 Page 18510)