

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION C C for 19 & 20 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6381-82)

Set a post cor. of secs. 17, 18, 19 and 20, from which
A B.Oak 12" dia., bears S.55°E., 31 lks. dist.
A B.Oak 8" dia., bears N.6°E., 26 lks. dist.
A B.Oak 12" dia., bears N.45°W., 25 lks. dist.
A B.Oak 14" dia., bears S.35°W., 126 lks. dist.

GL0 survey by W.F. Briggs, Deputy Surveyor, under Special Instructions, dated Jan. 18, 1899 - (DCSO records Vol. 15 Page(s) 6411)

At established cor. secs. 17, 18, 19 and 20. Re-established said corner as per old witness trees all standing in the original position and by setting a new post, 3 ft. long, 4" sq., 24" in the ground for secs. 19 and 20, mkd: T29S S19 on SW.; R4W S20 on SE. face, with 5 notches on E. and 3 notches on S. edges.
I destroyed all marks referring to secs. 17 and 18.

Ben B. Irving, County Surveyor - Wit: John H. Markham, Jr.; Joe Pruitt - July 7, 1954 - C.S. File 45/234

Set a 1" x 36" Iron pipe in ground for the cor. from a down B.Oak S.35°W., 126 lks., chopped out and found scribe and B.Oak N.45°W., 25 lks., down and rotten.
Scribed two new trees:
12" Fir S.38 3/4°W., 33.7 ft. on level.
10" Fir S.45°E., 55.0 ft., slope.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-132

Found both bearing trees and brass cap as recorded by Irving in 1954. SE. BT, now dead.
New BT - 10" R.Fir bears S.69°E., 30.7 ft. scribed S20 T29S R4W CS BT.

BLM resurvey by Boyd W. Peterson, under Group #1394, Surveyed Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page(s) 18512)

The cor. of secs. 19 and 20 only, on the S. bdy. of Sec. 18, perpetuated and recorded by Irving in 1954, and further perpetuated and recorded by Byron in 1963, monumented with an iron post 1½" dia., firmly set, projecting 18" above ground, with brass cap mkd: (Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION CC for secs. 19 & 20 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>COUNTY SURVEYORS OFFICE T 29 S R 4 W S 18 S 19 S 20</p> <p>from which the remains of an original bearing tree A rotted Oak stump 15" dia., bears N.44°W., 25 lks. dist., no marks visible. (Rec. N.45°W.) and a bearing tree mkd. by Irving A Fir 16" dia., bears S.40°W., 51 lks. dist. with healed double blaze. and a bearing tree mkd. by Byron A Fir 15" dia., bears s.69°E., 47 lks. dist. with healed double blaze.</p>
<p>Found and used by B.Shaner, Feb. 1997 - M 124-43 and C.S. File 65/13-2A</p> <p>-----</p> <p>Note - Corner lies 100 ft. south of rock road on top of N.Myrtle - S.Myrtle divide and also at east edge of recent clear cut. 6 ft. steel fence post bears NW, 1.0 ft.</p>
<p>Dan Saily- For: Lone Rock Timberland Co. - 9/2021 - M180-11</p> <p>-----</p> <p>Found - County Surveyors Office brass cap marked T29S R4W S18 S19 S20 22" D.Fir bears S.69¾°E., 30.5 ft (record S.69°E., 31.02 ft) no visible face found, has BLM tag 14"x7' tall Fir stump bears S.40°W., 33.1 ft (record S.40°W., 33.66 ft) no visible face, has BLM tag. Badly rotten remains of Oak stump found at record N.44°W., 16.5 ft. No remaining evidence of scribe</p> <p>Note - Corner lies at NW corner of recent clear cut on East facing slope, 260 ft East of gravel BLM RD #29-4-20.0. Top of corner monument is 1.4 ft above ground level. Steel T-Post bears West 0.8 ft. We place 5½ ft. tall steel U-Post 0.3 ft East.</p>
<p>2</p>