

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1957, surveyed Oct. 1857 - (DCSO records Vol. 15 Page(s) 6384)

Set 1/4 sec. post, from which
A Laurel 10" dia., bears S.60°W., 26 lks. dist.
A Laurel 6" dia., bears N.37°E., 39 lks. dist.

GL0 survey by W.F. Briggs, Deputy Surveyor, under Special Instructions dated Jan. 18, 1899 - (DCSO records Vol. 15 Page(s) 6410-11)

I made a new post and witness trees, (the old post and witness trees still visible but badly decayed), to wit:
A Fir post, 3" sq., 3 ft. long, 24" in the ground, scribed 1/4 S17 on E. face; 1/4 S18 on W. face, from which
A Fir 8" dia., bears S.65°W., 33 lks. scribed 1/4 S18 BT.
A Fir 6" dia., bears N.40°E., 7 lks. scribed 1/4 S17 BT.

John H. Markham, Jr. - May 7, 1957 - C.S. File 42/270

Location of corner determined by proportional measurement.
At corner point, Set a 3/4" x 24" Iron rod, 18" in ground, from which
A 7" Fir bears S.40°W., 26.8 ft. mkd. 1/4 S18 BT.
A 10" Fir bears S.74°W., 28.6 ft. mkd. 1/4 S18 BT.
A live Laurel stump 30" dia., 7 ft. tall bears N.77°E., 53.0 ft. mkd. 1/4 S17 BT. This stump is on top of side ridge and on cat road.

Douglas Co. Surveyors Office - John M. Powell and crew - Oct. 15, 1970 - C.S. File 49/67-45

Found - 3/4" Iron rod at 1/4 corner.
7" D.Fir now 10", S.40°W., 26.0 ft., shows good scar and pitched over scribing.
10" D.Fir now 12", S.74°W., 28.6 ft., shows good scar.
30" Laurel stump, live, N.77°E., 53.0 ft. stump beginning to rot, some scribe marks visible.
New BT - 6" D.Fir, N.57°E., 9.7 ft. scribed 1/4 S17 CS BT.

BLM resurvey by Boyd W. Peterson, under Group #1394, Surveyed Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page(s) 18515-16)

The 1/4 sec. cor., determined from the remains of a bearing tree mkd. by Briggs:
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir stump 12" dia., bears S.65°W., 33 lks. dist. with scribe marks ¼ S18 B visible on opened double blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T 29 S R 4 W
¼
S 18 | S 17
1987

from which new bearing trees:

A Fir 7" dia., bears S.15°E., 23 lks. dist. mkd. ¼ S17 BT.

A Fir 17" dia., bears N.39½°W., 40 lks. dist. mkd. ¼ S18 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established at proportionate position as the ¼ sec. cor., and recorded by Markham in 1957, and perpetuated and recorded by Powell in 1970, bears N.45°31'00"E., 0.080 chs. dist., monumented with an iron threaded bolt, 3/4" dia., firmly set, projecting 8" above ground, from which bearing trees mkd. by Markham:

A Fir 17" dia., bears S.43¼°W., 39 lks. with healed face.

A Fir 19" dia., bears S.76°W., 43 lks. dist. with healed face.

and a bearing tree mkd. by Powell:

A Fir 9" dia., bears N.52¼°E., 14 lks. dist. with healed double blaze.

Brent Knapp - For: Lone Rock Timber Co. - 11/2022 - M181-51

(Condition report)

Found - Brass cap per DCSO records

15" Fir, S.15°E., 15.2', healed scar.

22" Fir, N.39°W., 26.4', healed scar.

3/4" iron bolt, N.45°31'E., 5.28'

21" Fir, S.43°W., 25.7', healed scar.

13" Fir, N.53°E., 9.2', healed double blaze.