

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, under Contract #73, dated June 8, 1857 - (DCSO records Vol. 15 Page(s) 6385-86)

An Oak 15" dia., cor. secs. 5, 6, 7 and 9, from which
 An Oak 10" dia., bears N.85°W., 68 lks. dist.
 An Oak 15" dia., bears S.87°W., 87 lks. dist.
 An Oak 12" dia., bears N.30°E., 50 lks. dist.
 An Oak 6" dia., bears S.80°E., 88 lks. dist.

Witness trees found standing in GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 - (DCSO records, Vol. 15 Page 6398)

GLO survey by W.F. Briggs, Deputy Surveyor, under Special Instructions dated Jan. 18, 1899, found "Oak, 15" for post. Witness trees still standing" - (DCSO Records, Vol. 15 Page 6415)

Frank Cain, County Surveyor - Wit: F.J. Cole; J.T. Black; Wm. Berdine; W.H. Lawrance - May 1915 - Vol. 2 Pg. 231 (and "old" corner book, pg. 121)

Renew from stumps of original witness trees, from which
 A Fir 37" dia., bears S.34 3/4°W., 151 lks.
 A Fir 42" dia., bears N.37°W., 151 lks.
 A Fir 18" dia., bears N.39 1/4°E., 36 lks.
 A Fir 16" dia., bears S.73°E., 39 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-115

Found - All BTs as recorded by Cain, 1915.
 SE. and NE. BTs now stumps, show scribing.
 NW. and SW. BTs, show scars.

Set Brass cap at cor. mkd: County Surveyors Office

T	29	S	R	4	W
		S	6	S	5
		S	7	S	8
					1963

New BTs -15" R.Fir bears S.33°W., 16.9 ft. scribed S7 T29S R4W CS BT.
 14" R.Fir bears N.18°W., 22.4 ft. scribed S6 T29S R4W CS BT.
 12" R.Fir bears N.8°E., 12.8 ft. scribed S5 CS BT.
 No trees near to SE.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Gregory Quibell, Deputy - John Powell, Karen Reed, crew - April 4, 1982 - C.S. File 61/30-22

-
- Found - 1½" I.P. with 1963 DCSO brass cap, properly marked. Cap protrudes 11".
- 15" Fir now 18" stump with heavily pitched over face bears S.33°W., 15.8 ft. (Rec. 16.9 ft.)
 - 14" Fir now 14" snag 20 ft. tall with heavily pitched over face bears N.21°W., 21.4 ft. (Rec. N.18°W., 22.4 ft.)
 - 12" Fir now 12" rotted stump with scribed "BT" visible on unhealed face, bears N.6½°E., 13.2 ft. (Rec. N.8°E., 12.8 ft.)
- New BTs -3" Madrone bark scribed "S6 CS BT" bears N.83°W., 14.5 ft.
- 4" Madrone barks scribed "S5 CS BT" bears N.23°E., 10.4 ft.
 - 4" Madrone scribed "S8 CS BT" in double blaze bears S.52°E., 6.1 ft.
 - 4" Madrone bark scribed "S7 CS BT" bears S.36°W., 25.4 ft.

Sketch in file.

Fd. OK, March 1998 by D. Edwards - M 128-32

Fd. & used on BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19797-8)