

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 203400

PRIMARY CORNER DESCRIPTION C C for Secs. 17 & 18 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.F. Briggs, Deputy Surveyor, under special instructions dated Jan. 18, 1899 - (DCSO records Vol. 15 Page(s) 6411-12)

I set closing corner to secs. 17 and 18, at the point of intersection, to wit:
A Fir post 3" sq., 3 ft. long, 24" in the ground, scribed CC S17 on NE. face; CC S18 on NW. face; T29S R4W on SE.; and SW. faces, from which
 A B.Oak 18" dia., bears N.68°E., 85 lks. scribed CC S17 T29S R4W BT.
 A Fir 10" dia., bears N.68°W., 33 lks. scribed CC S18 T29S R4W BT.
Old corner to secs. 19 and 20 bears S.89°30'W., 3.08 chs.

Ben B. Irving, County Surveyor - Wit: John H. Markham, Jr.; Joe Pruitt - July 7, 1954 - C.S. File 45/234

Set a 1" x 36" iron pipe with brass cap 14" above ground from original BT, 20" Fir N.68°W., 30 lks., chopped out, in good condition. Marked two new bearing trees:
 A 12" Fir N.79°11'W., 49.1 ft. mkd. T29S R4W S18 CC CS BT
 A 12" Fir N.43°33'E., 21.1 ft. mkd. T29S R4W S17 CC CS BT

BLM resurvey by Boyd W. Peterson, under Group #1394, Surveyed Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page(s) 18516-17)

(41.270 chs.)
The original closing cor. of secs. 17 and 18, perpetuated and recorded by Irving in 1954, monumented with an iron post, 1¼" dia., firmly set, projecting 16" above ground, with brass cap mkd. County Surveyors Office T29S R4W S18 S17, from which the remains of an original bearing tree:
 A sawed Fir stump 22" dia., bears N.66¼°W., 30 lks. dist. with partially healed blaze. (Rec. N.68°W., 33 lks.)
and the remains of bearing trees mkd. by Irving:
 A Fir 18" dia., bears N.42½°E., 33 lks. dist. with healed double blaze.
 A sawed Fir stump 12" dia., bears N.55°W., 76 lks. dist., with scribe marks BT visible on bark and healed blaze.

(41.290 chs. S.0°36'00"W)
True point for the closing cor. of secs. 17 and 18, at intersection with the N. bdy. of sec. 20.
Set a stainless steel post 28" long, 2½" dia., 22" in the ground, with brass cap mkd:
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 203400

PRIMARY CORNER DESCRIPTION C C for Secs. 17 & 18 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T 29 S R 4 W
C C
S 18 | S 17
S 20
1987

from which

A Fir 15" dia., bears N.73°W., 54½ lks. dist. mkd. T29S R4W CC S18 BT.

A Fir 18" dia., bears N.15°E., 55 lks. dist. mkd. T29S R4W CC S17 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

(From this point, the cor. of secs. 19 and 20 only, bears N.89°39'00"W., 3.060 chs.)

Dan Saily- For: Lone Rock Timberland Co. - 9/2021 - M180-11

Found - 1988 BLM brass cap marked T29S R4W CC S18 S17 S20
24" D.Fir bears N.16¼°E., 36.6 ft (record N.15°E., 36.3 ft) well healed face and BLM tag
26" D.Fir bears N.73½°W., 35.5 ft (record N.73°W., 35 97 ft) well healed face and BLM tag
County Surveyors office brass cap marked T29S R4W S18 S17 bears North 1.15 ft. Top of corner monument is 1.25 ft above ground level
BTs for county brass cap
13"x5' tall D.Fir stump found at record N.55°W., 50.16 ft. Partially visible scribe and BLM tag
24" D.Fir bears N.42½°E., 21.7 ft (record N.42½°E., 21.78 ft) well healed face and BLM tag.
22"x4' tall D.Fir stump found at record N.66¼°W., 19.8 ft. Open burned face with no visible scribing.

Note - Corner lies at North edge of recent clear cut on South facing slope approximately 150 ft South of gravel BLM RD #29-4-20.0. Top of BLM corner monument is 0.3 ft above ground level. We place 5½ ft. tall steel U-Post 0.4 ft East.

BT distances are to an aluminum nail in the side center and bearings were derived from angular measurements to an aluminum nail in the face of the tree.

Fd as per rec. 11/2022 - B. Knapp - M181-51