

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6358)

-----  
Set ¼ sec. post at proper distance, from which  
A Laurel 12" dia., bears S.50°E., 39 lks. dist.  
A B.Oak 8" dia., bears N.40°W., 30 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 15 Page(s) 6406)

-----  
¼ sec. cor. post is gone and both bearing trees are standing, but the Laurel in the SE. is dead. I restore this corner by setting a W.Oak post, 3 ft. long, 3" sq., 24" in the ground, marked: ¼ S on N. face, from which  
A Laurel 24" dia., bears N.70°E., 63 lks. dist. mkd. ¼ S BT.  
A B.Oak 10" dia., bears N.40°W., 30 lks. dist. mkd. ¼ S BT  
The old bearing tree, whose marks being dim, I renew.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7097)

-----  
The ¼ sec. cor. on S. bdy. of sec. 32, which is a W.Oak post, 3" square, firmly set in the ground, marked ¼ S. on N. face, from which  
A Laurel 24" dia., bears N.70°E., 63 lks. mkd. ¼ S BT.  
A B.Oak 10" dia., bears N.40°W., 30 lks. mkd. ¼ S BT.

Survey by G.A. Barnhart - Wit: Weber and Stubblefield - June 1947 - C.S. File 40/19C

-----  
Found old BT, an 8" Oak (dead) and 24" Laurel (in good condition). From Laurel, measured S.70°W., 63 lks. and set a bottle and 4" x 4" Oak post for ¼ cor., from which  
A 24" Laurel bears N.70°E., 41.6 ft.  
A 10" Fir bears N.59°30'E., 2.9 ft.  
A 12" Fir bears N.11°00'W., 14.5 ft.

John H. Markham, Jr. - For: Markham & Sons Lbr. Co. - Dec. 5, 1949 - C.S. File 40/238

-----  
As determined from original BT.  
A Laurel 36" dia., bears N.70°E., 41.5 ft., scribe legible  
A dead B.Oak snag bears N.40°W., 19.8 ft. scribe legible.  
At corner point, Set ¾" x 24" I.P., 14" in ground. Six feet to the North, found 4"x4" post mkd. ¼ S32, which I moved to corner point.  
from which bears: (Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 9" Fir bears North, 7.0 ft. mkd. ¼ S32 BT.  
A 12" Fir bears N.15°W., 21.0 ft. mkd. ¼ S32 BT.  
These trees witnessed the post I fd; I did not remark them.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - May 1963 - C.S. File 52/126  
-----  
Found - 3/4" I.P. at cor. and both BTs as recorded by Markham, now down. Both original BTs found. NW BT down.  
New BTs -9" Fir bears N.56°W., 7.9 ft. scribed ¼ S32.  
12" R.Fir bears N.83°E., 2.5 ft. scribed ¼ S32 CSBT

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20098-9)  
-----  
The ¼ sec. cor. of sec. 32 only, perpetuated by Barnhart, in 1947, further perpetuated by Markham, in 1949, further perpetuated by Byron, in 1963, monumented with an iron pipe, 1" diam., firmly set, projecting 8" above ground, from which the remains of an original bearing tree:  
A sawed madrone stump, 48" diam., bears N.70°E., 63 lks., with no marks visible.  
and the remains of bearing trees mkd. by Byron  
A fir, 20" diam., bears S.88 3/4°E., 4 lks., with healed double blazes.  
A fir snag, 11" diam., bears N.57½°W., 12 lks., with scribe marks ¼ S32 CS BT visible on open double blazes.  
At the corner point  
Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, directly over the iron pipe, with brass cap mkd.  
T29S R4W  
¼ S 32  
T30S R4W  
1994  
from which a new bearing tree  
A fir, 17" diam., bears N.36½°W., 25½ lks., mkd. ¼ S32 BT.  
Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

David Edwards - For: Roseburg Resources Co - 4/2018 - M174-36  
-----  
Fd BC & 2 BTs: A 22" dia., Fir bears S.88¼°E., 2.6'  
A 21" dia., Fir bears N.36½°W., 16.8': Both with healed blaze