

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 20 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6382)

-----  
Set ¼ sec. post at average dist., from which  
A Laurel 16" dia., bears S.70°E., 22 lks. dist.  
A Laurel 4" dia., bears N.25°E., 25 lks. dist.

GLO resurvey by W.F. Briggs, under Special instructions dated Jan. 18, 1899 "found cor. which is in good state of preservation." - (DCSO records Vol. 15 Page(s) 6413)

BLM resurvey by Boyd W. Peterson, under Group #1394, Surveyed Aug. 1987/Jan. 1988 (DCSO records Vol. 48 Page(s) 18513)

-----  
Point for the ¼ sec. cor. of sec. 20 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 4 W

-----  
¼ S 20  
1987

from which

A Fir 6" dia., bears S.57°E., 17 lks. dist. mkd. ¼ S20 BT.  
A Cedar 14" dia., bears S.55½°W., 60 lks. dist. mkd. ¼ S20 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Found OK by B. Shaner, Feb. 1997 - M 124-43 & C.S. 65/13-2D