

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 240540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Francis L. Ingram - For: C.E. Barnhart, etal - Dec. 1973 - M 51-68

Set 1/2" I.R. at center of sec. 8 by intersection.

Douglas Co. Surveyors Office - Gary Langlitz and P. Earle - May 3, 1974 - C.S. File 56/51

Found - 1/2" Iron rod set at point of intersection of lines from opposite 1/4 corners of sec. 8.
Set brass cap mkd. County Surveyors Office
T 29 S R 4 W
C 1/4 S 8
1974

Deposit Iron rod alongside brass cap.
New BTs -7" Fir bears S.8°E., 29.6 ft. scribed "T29S R4W C1/4 S8 CS BT"
6" Fir bears S.87°E., 18.4 ft. scribed "C1/4 S8 CS BT"
This corner is located on the edge of a road cutbank, on the easterly side of a dirt easement road and directly beneath a high voltage electrical transmission line.

Douglas County Surveyors Office - Gregory Quibell, Deputy - T. Plouff, crew - July 10, 1982 - C.S. File 61/36-25

Found - 2" Brass cap firmly set, protruding 4" out of ground, properly mkd.
1/2" I.Rod along South edge of brass cap, flush with the ground.
7" now 8" Fir, now stump 6 ft. high with scribed "T29S R4W C 1/4 S8 CS BT" visible in partially healed double blaze, bears S.8°E., 29.6 ft.
6" now 7" Fir now stump 6 ft. high with scribed "C 1/4 S8 CS BT" visible in partially healed double blaze bears S.88 1/2°E., 18.4 ft. (Rec. S.87°E.)
New BTs -10" Fir scribed "C 1/4 S8 CS BT" in double blaze bears S.38°E., 40.0 ft.
14" Fir scribed "C 1/4 S8 CS BT" in double blaze bears N.77°W., 42.2 ft.
Sketch in CS file.

Fd. OK, Dec. 1994, by L. Dolan - M 121-29
Fd. OK, May 1996 by Barnhart - M 123-62
Found OK by D. Beedle, May 2002 - M140-15