

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec Cor for 32 and 33 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6358)

Set a post at proper distance, cor. of secs. 4, 5, 32 and 33, from which

- A Laurel 4" dia., bears S.30°E., 34 lks. dist.
- A Laurel 14" dia., bears N.65°E., 43 lks. dist.
- A Laurel 4" dia., bears S.45°W., 25 lks. dist.
- A Laurel 4" dia., bears N.60°W., 13 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 15 Page(s) 6406-07)

Set a Laurel post to cor. of secs. 32 and 33, 4½ ft. long, 4" sq., 24" in the ground, marked: T29S R4W on N.; S33 on E.; S32 on W. face, and 4 notches on E. and 2 notches on W. faces, from which

- A Laurel 6" dia., bears N.30°E., 89 lks. dist. mkd. T29S R4W S33 BT.
- A Pine 10" dia., bears N.72°W., 49 lks. dist. mkd. T29S R4W S32 BT.

(From this cor. I run a line North, 40.00 chs. but found no indication of any marks of survey, showing that a line had been initiated from this corner, confirming my belief that Deputy Ford omitted a good deal of field work in the rough mountains, which I have noticed before in private surveys.)

Survey by John H. Markkham, Jr. - Wit: Geo. Vaughn; Don Weathers - April 7, 1951 - C.S. File 40/304-1

Determined by Old BT.
A Laurel 15" dia., bears N.30°E., 59.0 ft. (OBT)
A Pine 20" dia., bears N.12°W., 32.0 ft. (OBT)
I remark both BTs.
At corner point Set 1" x 24" Iron pipe.

Survey by Jack L. Sheppard, LS #180 - Jan/Feb. 1955 - C.S. File 41/337

Found 1" I.P. set from original BTs.
14" Laurel N.30°E., 58.7 ft. Old bearing tree.
20" Pine N.72°W., 32.3 ft. Old bearing tree.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300100

PRIMARY CORNER DESCRIPTION Sec Cor for 32 and 33 only (South)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The cor. of secs. 32 & 33, perpetuated by Markham, in 1951, further perpetuated by Jack L. Sheppard, in 1955, monumented with an iron pipe, 1¼" diam., firmly set, projecting 12" above ground, from which the original bearing trees:

A madrone, 21" diam., bears N.31½°E., 89 lks., with fragmentary scribe marks visible on open partially decayed blaze. (Record, N.30°E.)

A pine, 24" diam., bears N.9 3/4°W., 49 lks., with healed blaze. (Record, N.72°W.)

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, directly over the iron pipe, with brass cap mkd.

T29S R4W
S 32 | S 33
S 5
T30S R4W
1994

from which a new bearing tree

A fir, 18" diam., bears N.12°E., 48 lks., mkd. T29S R4W S33 BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.