

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6374)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears N.8°W., 28 lks. dist.
A Laurel 24" dia., bears S.20°E., 50 lks. dist.

Survey by Jack L. Sheppard, LS #180 - Jan/Feb. 1955 - C.S. File 41/337

Set 2" Iron pipe. (halfway between sec. corners)
Scribed two trees:
30" Fir N.19°E., 9.4 ft. scribed ¼ S33 LS 180 BT.
18" Cedar S.26°W., 16.0 ft. scribed ¼ S32 LS 180 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-137

Found - 2" Iron pipe.
30" Fir N.19°E., 9.4 ft., OK, shows scribing.
18" Cedar S.26°W., 16.0 ft., stump.
New BT - 18" Cedar N.70°W., 41.5 ft. scribed ¼ S32 CS BT.

Fd. Ok by Ken Hoffine, July 2005 - M148-23

Douglas Co. Surveyors Office - Stephen J. Flause - John Pike - 8/16/2005 - C.S. File 67/10-45

Found - 2" O.D. iron pipe badly bent, top leans SSE approx. 15". Pipe is in 2 pieces. A 1½" pipe is stuck inside the 2" pipe totaling 42" in length
30" D.Fir now 33"x6 ft. tall stump capped w/alum. and bark sawn smooth healed blaze visible bears N.19°E., 9.4 ft. probable face meas.)
18" now 27" I.Cedar healed double blaze vis. bears N.70°W. 41.0 ft (rec. N.70°W. 41.5 ft) Byron 1963
Root hole fd. at approx rec. brg. & dist. (Rec. S.26°W., 16.0 ft.) Sheppard 1955

New - 2 3/8" brass cap on 1¼" O.D. x 30" iron pipe is set in referenced plumb position of bent 2" iron pipe. The 2 pieces of pipe found are reset on the East & West sides. BC/IP projects from ground 6".
Cap mkd: DOUGLAS CO. SURVEYORS OFFICE

T 29 S
¼ S 32 | S 33
R 4 W
2005

cont. next pg.

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

New BTs- 8" W.Fir, double blazed & scribed "¼ S32 CS BT"
bears S.64½°W., 18.7 ft.
14" dia., D.Fir double blazed & scribed "¼ S32 CS
BT" bears N.6°W., 35.4 ft.
6" dia., I.Cedar double blazed & scribed "X CS BT"
bears S.53½°E., 33.6 ft.
Note - Lies on North facing slope.
Decl. 16¾°E.

Fd. as per record, 4/2018 - By D. Edwards, M174-36