

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6377)

Set ¼ sec. post, from which
A Laurel 4" dia., bears S.25°E., 50 lks. dist.
A Laurel 5" dia., bears S.40°W., 33 lks. dist.

GLO survey by W.F. Briggs, Deputy Surveyor under Special Instruction, dated Jan. 18, 1899 (DCSO records, Vol. 15 Page 6413)

¼S cor. on old blazed line.
Re-established cor. by setting new post, 3 ft. long, 3" sq., 24" in the ground for said ¼ sec. cor., mkd. ¼ S16 on E.; S17 on W. face, in the original position.

W.H. Wood, Deputy Co. Surveyor - crew, W.S. Crear; A.C. Redifer - Wit: P.R. Weaver; G.M. Dyer; W.H. McClain; W.O. Suoffard - Nov. 3-6, 1925 - Vol. 3 Pg. 229 (and "old" corner book, pg. 123)

Found Laurel S.50°E., 33 lks. and stump S.25°E., 5 lks.
Set 4 x 4 x 2.5 ft. Cedar post, mkd. ¼ 16-17 C.S.
Marked -Red Fir 15" dia., S.43°30'E., 50 lks. "¼ S16 CSBT"

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - March 18, 1958 - C.S. File 42/345-7

Cor. determined by O.B.T. and post:
20" Fir stump, logged, bears S.43½°E., 33.0 ft., found scribe. O.B.T.
At corner point, found 4" x 4" wood post scribed ¼ S16 ¼ S17.
I set 1" x 30" I.P., from which
5" Laurel bears S.70°E., 12.1 ft. mkd. ¼ S16 T29S R4W BT
4" Cedar bears S.7°E., 34.2 ft. mkd. ¼ S16 BT.
5" Laurel bears S.54°W., 12.4 ft. mkd. ¼ S17 T29S R4W BT
11" Fir bears N.45°W., 10.8 ft., bark scribed ¼ S17 BT.
A N-S fence bears West 14.0 ft.
Sec. cor. 9-16 only bears North 2206.0 ft. (21°10'Var.)

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-129

Found - I.P. and post at corner.
All BTs as recorded by Markham. Laurel to SE. is dead. We remark 12" R.Fir N.45°W., 10.8 ft. "¼ S17 CS BT"
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

We destroy scribing on 6" Laurel S.54°W., 12.4 ft.
New BT - 8" R.Fir bears N.32°E., 6.3 ft. scribed ¼ S16 CS BT.

BLM resurvey, by Boyd W. Peterson, under special instructions dated August 18, 1986, under Group #1346, Surveyed Sept./Dec. 1986 (DCSO records Vol. 48 Page(s) 18508)

The ¼ sec. cor., perpetuated and recorded by Markham in 1958, from evidence no longer in existence, further perpetuated and recorded by Byron in 1963, monumented with an iron pipe 1" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Markham:

A Cedar 9" dia., bears S.6½°E., 52 lks. dist. with fragmentary scribe marks visible on partially healed blaze.

A Fir 18" dia., bears N.44½°W., 16 lks. dist. with healed double blaze.

and a bearing tree mkd. by Byron:

A Fir 14' dia., bears N.31¼°E., 9 lks. dist. with healed double blaze.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the iron pipe, with brass cap mkd:

T 29 S R 4 W
 ¼
 S 17 | S 16
 1987

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

Fd. OK, Aug. 1993 by B. Shaner - RM 3-79