

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Cor. for Secs. 9 and 16 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6377)

-----  
Set a post cor. secs. 8 and 9, and 16 and 17, from which  
A Laurel 12" dia., bears S.85°E., 25 lks. dist.  
A Laurel 4" dia., bears N.15°E., 92 lks. dist.  
A B.Oak 9" dia., bears N.65°W., 42 lks. dist.  
A B.Oak 16" dia., bears S.55°W., 14 lks. dist.

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6395-96)

-----  
Witness trees all standing. SET new post.  
A Laurel 12" dia., bears S.85°E., 25 lks. dist.  
A Laurel 4" dia., bears N.15°E., 92 lks. dist.  
A B.Oak 9" dia., bears N.65°W., 42 lks. dist.  
A B.Oak 16" dia., bears S.55°W., 14 lks. dist.

GL0 survey by W.F. Briggs, Deputy Surveyor, under Special Instructions, dated Jan. 18, 1899 - (DCSO records, Vol. 15 Page 6409)

-----  
Intersect blazed line 5.24 chs. N.7°7'E., of established cor. of secs. 8, 9, 16 and 17. Witness trees all standing. Set new post as per witness trees called for: Secs. 9 and 16, T29S R4W, to wit:  
A Laurel 4" dia., bears N.15°E., 92 lks.  
A Laurel 12" dia., bears S.85°E., 25 lks.  
I destroyed all marks appertaining to Secs. 8 and 17.

W.H. Wood, Deputy Co. Surveyor - Crew, W.S. Crear; A.C. Redifer - Wit: P.R. Weaver; G.M. Dyer; W.H. McClain; O.W. Suoffard - Nov. 2-6, 1925 - Vol. 3 Pg. 229

-----  
Bearing trees rotten and dead. Marked new trees:  
A Fir 12" dia., bears N.48°30'W., 28 lks. "S8 BT CS"  
A Fir 12" dia., bears S.9°00'W., 34 lks. "S17 BT CS"  
A Fir 10" dia., bears S.44°00'E., 43 lks. "S16 BT CS"  
A Fir 9" dia., bears N.19°00'E., 40 lks. "S9 BT CS"

Claude Kerr - June 6, 1950 - C.S. File 40/252

-----  
Found all four small Fir BTs.  
Put 4" x 4 ft. Cedar post in at corner and scribed it with S8 S9 S16 and S17.

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9 & 16 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

John H. Markham, Jr. - Wit: R.G. Boyd - For: Stomar Lbr. Co.  
Sept. 10, 1957 - C.S. File 42/298-2

-----  
NW Cor. sec. 16 and SW cor. Sec. 9 only, as determined by old bearing trees:

20" Fir S.9°W., 22.4 ft.

10" Fir S.43°E., 28.4 ft.

There was 4 more old bearing trees either dead or logged.

At corner point found scribed post and set 3/4" x 22" Iron bar, from which

18" Laurel bears S.84°E., 18.2 ft. mkd. S16 T29S R4W BT

12" W.Oak bears S.26°W., 38.5 ft. mkd. S17 BT.

28" Laurel bears S.14°W., 90.0 ft. mkd. S17 T29S R4W BT

Closing cor. 8 & 17 bears N.9°E., 345.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April/May 1963 - C.S. 52/126-123

-----  
Found - 3/4" Iron bar.

18" Laurel, now 20" S.84°E., 18.2 ft. Rescribed S16 CS BT.

28" Laurel now 30" S.14°W., 90.0 ft., OK.

New BT - 15" Fir N.6°E., 95.0 ft. rescribed T29S R4W S9 CS BT

Referenced out for Round Prairie Road, J. Powell, DCS0, June 28, 1973

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July/Oct 1977 (DCS0 records Vol. 39 Page(s) 15886-87)

-----  
The cor. of secs. 9 and 16 only, perpetuated and recorded by Wood in 1925, from evidence no longer in existence, and further perpetuated and recorded by Markham in 1957, monumented with an iron bar, 3/4" dia., firmly set, projecting 3" above ground. This corner is accepted as the best available evidence of the original corner position, from which the remains of the bearing trees mkd. by Wood:

A Fir snag 7" dia., bears N.19°E., 40 lks. dist. with scribe marks S9 CS visible on partially healed blaze.

A Fir 17" dia., bears S.43°E., 44 lks. dist. with healed blaze.

A Fir 32" dia., bears S.9°W., 36 lks. dist. with healed blaze.

A Fir stump 16" dia., bears N.48½°W., 28 lks. dist. no marks visible.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 9 and 16 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

and the remains of bearing trees mkd. by Markham:  
 A Madrone 25" dia., bears S.85°E., 37 lks. dist. with scribe marks T29S R4W S16 visible on bark and scribe marks CC S 6 CS BT by James Byron in 1963, visible on partially healed blaze.  
 A madrone 30" dia., bears S.13¼°W., 138 lks. dist. with scribe marks T29S R4W S17 visible on partially healed blaze and BT visible on bark.  
 An Oak snag 12" dia., bears S.26°W., 58 lks. dist. with scribe marks S17 BT visible on partially healed blaze.  
 and a bearing tree mkd. by Byron in 1963:  
 A Fir 20" dia., bears N.4¼°E., 144 lks. dist., with illegible scribe marks visible on partially healed blaze.  
 At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron bar, with brass cap mkd: T 29 S R 4 W  

S 17 | S 9  
       | S 16  
       1969

Douglas Co. Surveyors Office - R.B. Kimberling, Deputy - P.L. Earle; F.C. Silagy, crew - march 21, 1978 - C.S. File 59/46-58  
 -----  
 Found - A 2" I.P. with standard BLM brass cap set 8" above ground 1969, properly marked.  
 A 12" now 26" Madrone (OBT) bears S.85°E., 16.5 ft. with scribing "CC S16 CS BT" in a partly healed single blaze on the left side of a rotted out blaze.  
 A 16" now 18" Oak (OBT) is down, stump bears S.55°W., 9.2 ft. with a rotted out blaze.  
 A 20" now 27" D.Fir bears S.11°W., 23.2 ft. (Rec. S.9°W. 22.4 ft.) with a well healed blaze.  
 A 10" now 12" D.Fir bears S.41½°E., (Rec. S.43°E) 28.4 ft. with a well healed blaze. I open to find scribing has been chopped out.  
 A 12" now 14" Oak is down. Stump bears S.29°W., (Rec. S.26°W.) 38.5 ft. with scribing "S17 BT" in a double blaze.  
 A 28" Madrone (Laurel) bears S.16½°W., 91.3 ft. (Rec. S.14°W., 90.0 ft.) with scribing "29 R" in partly healed single blaze.  
 A 15" now 20" Fir snag, 30 ft. high, bears N.6°E., 94.3 ft. (Rec. 95.0 ft.) with scribing "T29S R4W S9" in a partly healed double blaze.  
 No new monument set.  
 New Accessories: (Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9 and 16 only

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

|  |
|--|
| <p>A 9" D.Fir bears N.36°E., 10.8 ft. I double blaze and scribe "T29S R4W CS BT".<br/>A 5/8" I.Rod bears S.22°E., 61.1 ft. in line with a "PK" nail in an 8" D.Fir which bears S.22°E., 103.2 ft.<br/>Corner is 20 ft. South of South edge of unit, 346 ft. South of CC for secs. 8 and 17. 100 ft. East of BLM Rd. #29-4-17.</p>  |
| <p>Cor. Fd. and used in BLM resurvey by Boyd W. Peterson, under Group #1394, surveyed Aug. 1987/Jan. 1988 - (DCS0 records, Vol. 48 Pages 18508-09)</p>   |
| <p>BLM survey by Scott Toldness - PLS 90216 - Glahe &amp; Associates Professional Land Surveyors - 2024 - M185-29 A/D<br/>-----<br/>Found - 3¼" BLM Brass cap on a 2½" I.P. 0.6" above ground.<br/>15" Fir bears N.36°E. 10.8' with healed blaze and BT tag.<br/>Madrone stump 15' tall bears S.85°E. 16.5' with healed blaze and BT tag.<br/>24" Fir bears S.43¼°E. 28.4', healed blaze, BT tag and K-tag.<br/>35" Fir bears S.8½°W. 23.2', healed blaze, BT tag.<br/>30" Madrone bears S.14¾°W. 91.3' with healed blaze<br/>5/8" Iron rod bears S.23°E. 60.98'<br/>New - Added paint, nails at side center, and BT tags to living BTs.</p> |
| <p> </p>   |