

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300506

PRIMARY CORNER DESCRIPTION C C for secs. 8 and 17 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.F. Briggs, Deputy Surveyor, under Special Instructions dated Jan. 18, 1899 - (DCSO records, Vol. 15 Page 6410)

-----  
Set a closing corner for sections 8 and 17, at point of intersection, to wit:  
A Fir post 3" sq., 3 ft. long, 24" in the ground, scribed CC S8 on NW. face; CC S17 on SW. face, T29S R4W on NE. face, with 4 notches on S. and E. edges, from which  
    A Fir 10" dia., bears S.33°W., 32 lks. scribed CC S17 T29S R4W BT.  
    A Laurel 6" dia., bears N.42°W., 95 lks. scribed CC S8 T29S R4W BT.  
Old corner to secs. 9 and 16 bears S.7°7'W., 5.24 chs.

Survey by John H. Markham, Jr. - For: Stomar Lbr. Co. - Wit: R.G. Boyd - Sept. 10, 1957 - C.S. File 42/298-1

-----  
Corner determined by old bearing trees:  
    20" Fir bears S.33°W., 21.1 ft.  
    14" Laurel stump bears N.42°W., 72.0 ft.  
At corner point, SET 3/4" x 20" Iron pipe, from which  
    12" Fir bears N.30°E., 53.3 ft. mkd. S9 BT.  
    24" Laurel bears N.49°E., 106.5 ft. mkd. S9 T29S R4W BT  
    32" Laurel bears S.38°E., 61.2 ft. mkd. S9 T29S R4W BT.  
Closing cor. for 9 and 16 bears S.9°W., 345.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-123

-----  
Found - 3/4" I.Pipe.  
    12" Fir, now 13" N.30°E., 53.3 ft. OK.  
    32" Laurel S.38°E., 61.2 ft.  
New BT - 24" Fir S.15°W., 45.7 ft. scribed CC T29S R4W CSBT.

Referenced out for Round Prairie Rd. - J. Powell, DCSO, June 28, 1973 - C.S. File 59/30

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July/Oct 1977 (DCSO records Vol. 39 Page(s) 15887)

-----  
The closing cor. of secs. 8 and 17, on the W. bdy. of Sec. 9, perpetuated and recorded by Markham in 1957, monumented with an iron pipe, 3/4" dia., firmly set, projecting 4" above ground, from which the remains of the original bearing trees;  
  
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 8 and 17 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 25" dia., bears S.29 3/4°W., 32 lks. dist. with healed blaze. (Rec. S.33°W.)  
 and bearing trees mkd. by Markham:  
 A Fir 15" dia., bears N.28 3/4°E., 80 lks. dist. with healed blaze and scribe marks BT visible on bark blaze.  
 A Madrone 28" dia., bears N.47 3/4°E., 159 lks. dist. with scribe marks 29 R4 S9 visible on partially healed blaze.  
 A Madrone 37" dia., bears S.42¼°E., 81 lks. dist. with decayed blaze, no marks visible.  
 and a bearing tree mkd. by Byron in 1963:  
 A Fir 22" dia., bears S.12 3/4°W., 70 lks. dist., with illegible scribe marks visible on open blaze.  
 At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd:

T	29	S	R	4	W
CC		$\frac{S}{S}$	$\frac{8}{17}$		S 9
					1969

Douglas Co Surveyors Office - R.B. Kimberling, Deputy - P.L. Earle, F.C. Silagy, crew - March 21, 1978 - C.S. File 59/46-57  
 -----  
 Found - 1969 Cadastral brass cap on a 2" I.P. set 8" above ground, properly marked.  
 A 10" now 25" D.Fir (OBT) bears S.33°W., 21.1 ft. with a well healed blaze.  
 A 12" now 16" Fir stump bears N.32°E., (Rec. N.30°E.) 53.3 ft. with scribing "RS 9" in a partly healed blaze.  
 A 24" Madrone (Laurel) stump bears N.51°E., 104.2 ft. (Rec. N.49°E., 106.5 ft.) with scribing "9S R" in partly healed blaze.  
 A 32" Madrone (Laurel) stump bears S.38°E., 55.8 ft. (Rec. 61.2 ft.) with a partly healed rotted blaze.  
 A 24" D.Fir bears S.16°W., 45.2 ft. 9Rec. S.15°W., 45.7 ft.) with a well healed single blaze.  
 No new monument set.  
 New BT - A 6" D.Fir bears N.5°W., 4.9 ft. I double blaze and scribe "CC T29S R4W S8 CS BT".  
 Corner is 50 ft. East of Rd. #29-4-17 in a clearcut. BTs are almost the only trees standing on a -36° East slope. A steel fence post is 0.1 ft. West of corner.

(Cont. Next Page)

2



TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300506

PRIMARY CORNER DESCRIPTION C C for secs. 8 and 17 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates  
Professional Land Surveyors - 2024 - M185-29 A/D

-----

Found ok per record.

Set - 13" Fir bears N.19°W. 17.05' to a nail in right  
side center, snow blazed and scribed  
"T29SR4WS8BT."

New - Added paint, nails (per above locations), new tags  
and LS washer 90216 to all Bts.