

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6396)

Set Cedar post for the 1/4 sec. cor., from which
A Laurel 10" dia., bears N.66°E., 150 lks. dist.
A Laurel 16" dia., bears S.35°W., 20 lks. dist.

GLO survey by W.F. Briggs, Deputy Surveyor, under Special Instructions dated Jan. 18, 1899 - (DCSO records Vol. 15 Page(s) 6414)

I could not find any marks of 1/4 S on old line, measured West 4.96 chs. Intersect 1/4 S cor. as described by field notes from U.S. Surveyor General which I destroy.
Set new corner on true line to wit:
Fir post 3" sq., 3 ft. long, 24" in the ground scribed 1/4 S8 on W. face, from which
Laurel 4" dia., bears N.31°W., 23 lks. scribed 1/4 S8 BT.

Claude Kerr - June 6, 1950 - C.S. File 40/252

Found the Laurel bearing N.66°E., 150 lks. I reset the corner putting a 4" x 4 ft. Fir stake at corner and scribed it "1/4 S" on N. and S. sides, S9 on E. side and S8 on W. side.
I marked a new BT:
A 30" Fir bearing N.10°W., 14 lks.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15888)

Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 29 S R 4 W
 1/4
 S 8 | S 9
 1969

from which
A Cedar 13" dia., bears N.61°E., 24 lks. dist. mkd. 1/4 S9 BT.
A Cedar 12" dia., bears S.61°W., 12 lks. dist. mkd. 1/4 S8 BT.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024 - M185-29 A/D

Found - 3¼" BLM brass cap on a 2½" I.P 0.3' above ground.
18" Cedar bears N.70¼°E. (N.61°E.) 15.8' (24 lks)
to a nail with a healed blaze.
17" Cedar bears N.61°W. 7.9' (12 lks) to a nail
with a healed blaze.
New - Added paint, snow blaze, nails and LS washer 90216
at right side center of BTs.