

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6397)

-----  
Set Fir post for ¼ sec. cor., from which  
A Fir 40" dia., bears S.89°E., 33 lks. dist.  
A Fir 12" dia., bears N.20°W., 32 lks. dist.

Frank Cain, Co. Surveyor - May 1915 - Vol. 2 Pg. 225

-----  
Renew corner from original trees,  
A W.Fir 12" dia., bears N.10°W., 32 lks.  
A W.Fir 40" dia., bears S.79°E., 33 lks.  
Set an Oak post 4" x 4" x 3½ ft.

G.G. Stewart, Deputy Co. Surveyor - Feb. 1922 - M 2-4 and Vol. 3 Pg. 113

-----  
6" hewed Yew post. Original BTs.

Survey by Geo. J. Wenderoth - For: J Day - 11/1946 - M 28-78A

-----  
1¼" I.P.  
40" Fir S.89°E., 21.7 ft.  
12" W.Fir N.20°W., 21.1 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April/May 1963 - C.S. 52/126-118

-----  
Found - 1" I.P. at corner and both BTs as recorded by Frear.  
Orig. 12" now 30" W.Fir N.10°W., not N.20°W., 21.1 ft., shows scribe marks.  
Orig. 40" now 44" R.Fir S.79°E., not S.89°E., 21.8 ft., shows bark scribing.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 4 W  
¼ S5 | S4  
1963

New BT - Rescribe now 30" W.Fir N.10°W., 22.0 ft. ¼ S5 CS BT.

Fd. OK, April 1993 by G. Lang - M 118-13  
Fd. OK, April 1996 by G. Lang - M 125-24  
Fd. OK, July 2005 by M. Hamburger - M148-11

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Roseburg Resources - 10/2024 - M184-31  
-----  
Found - DCS0 brass cap  
A 30" fir w/HB bears N.10°W., 22.0'  
No other BT's of record remain.  
New BTs- A 7" Fir scribed "¼ S4 BT" bears S.50½°E., 24.0'  
An 11" Fir scribed "¼ S5 BT" bears N.81°W., 20.9'  
5.5 ft steel posts are set 2' S.1°30'W., on line  
and 2' S.82°30'E., on line.