

PRIMARY CORNER DESCRIPTION Cor to Secs 4 & 5; 32 & 33 T 28-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, Contract # 44 dated May 30, 1854  
(DCSO records Vol. 13 Pg. 5607).

-----  
Set post at proper distance for corner from which:  
A W.Oak, 10" dia. bears S.30°E., 61 lks. dist.  
A W.Oak, 6" dia. bears N.50°E., 61 lks. dist.  
A W.Oak, 30" dia. bears N.25°W., 44 lks. dist.  
A W.Oak, 4" dia. bears S.20°W., 90 lks. dist.

South Boundary of T.28-4, surveyed by W.H. Byars, Contract  
# 376 dated, Jan. 22, 1881. (DCSO records Vol. 13 Pg. 5613)

-----  
Set Oak post for sec. cor from which:  
A Fir, 8" dia. bears N.70°E., 85 lks. dist.  
A Fir, 30" dia. bears S.75°E., 1.31 chs. dist.  
A Fir, 8" dia. bears S.20°W., 1.51 chs. dist.  
A Pine, 7" dia. bears N.50°W., 35 lks. dist.  
Note: Per note in Byars 1881 survey "In the execution of this  
work I found that the old line established for the S bdy of  
this Township was glaringly at fault..." Byars set his own  
corners. See CS 63/166 BLM opinion file T28-4 (added 4/7/2010)

Frank Cain Co. Surveyor, witnesses, F.J. Cole, J.T. Black,  
Wm. Berdine. Surveyed for WlH. Lawrance. Recorded in Vol. 2  
Pgs. 222-226 & 231-232, also FB no.34 pgs. 14-24. May 1915.

-----  
Renew from original trees two orig. trees do not check.  
Set post from which original trees bear as follows:  
A Fir, 20" dia. bears N.70°20'E., 80 lks. dist.  
A Fir, 20" dia. bears N.82°15'E., 55 lks. dist.  
A Fir, 42" dia. bears S.72°30'E., 125 lks. dist.  
A Fir, 24" dia. bears S.17°25'W., 138 lks. dist.  
New Bt- A W.Oak 5" dia. bears N.59°W., (no dist. fnd. in rec.)

James W. Byron, Deputy Co. Surveyor, Mike Darby & William  
Stoffel. - April 1963 - C.S. File 52/126-120

-----  
Found - Angle iron fence post. (See M28-78A & C.S. 53/93)  
20" Fir, N.70°E., 52.8', now 28" good scar.  
20" Fir, N.82°E., 36.2', dead, found scribing.  
42" Fir, S.72°E., 82.5', cut down, shows scribing  
New BTs- 8" Laurel, S.41°W., 47.7'. Scribed T29S R4W S5 CSBT.  
10" Laurel, S.20°E., 31.9'. Scribed S4 CSBT.  
29" Fir, N.42°W., 31.2'. Scribed T28S R4W S32 CS BT.  
Note - Corner 1 foot east of north-south fence.

Found OK, May 1991 - R. Dolan, M 113-4.