

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 333100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 5 only, T30-4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 17 Page(s) 7081)

-----  
For the closing cor. of secs. 4 and 5, I set a Fir post 4½ ft. long, 4" sq., 24" in the ground, marked CC T30S R4W on S. face; S4 on E. face; S5 on W. face, with 4 notches on E. and 2 notches on W. faces, from which

A Fir 10" dia., bears S.44 ¾°E., 11 lks. dist. mkd. T30S R4W S4 BT.

A Fir 8" dia., bears S.27½°W., 30 lks. dist. mkd. T30S R4W S5 BT.

Survey by John H. Markham, Jr. - Wit: Geo. Vaughn; Don Weathers - April 7, 1951 - C.S. File 40/296-3

-----  
Determined by O.B.T.

A Fir 28" dia., bears S.45°E., 7.0 ft. (OBT)

A Fir 27" dia., bears S.33°W., 20.0 ft. (OBT)

I remark both trees.

At corner point, Set 1" x 24" Iron pipe.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20116)

-----  
True point for the closing cor. of secs. 4 and 5.

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T29S R4W

S 32

S 5 | S 4

C C

T30S R4W

1994

from which

A fir, 7" diam., bears S.19 ¾°E., 77 lks., mkd. T30S R4W S4 CC BT.

A cedar, 22" diam., bears S.42°W., 46 lks., mkd. T30S R4W S5 CC BT.

Deposit a white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, the original closing cor. of secs. 4 & 5, perpetuated by Markham, in 1951, further perpetuated by Warner, in 1957, bears N.0°43'27"E., 0.262 chs.; monumented with an iron pipe, 1¼" diam., firmly set, projecting 6" above ground, from which the remains of the original bearing trees:

A fir, 30" diam., bears S.44 ¾°E., 11 lks., with healed blaze.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 333100

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 5 only, T30-4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A root hole, bears S.27½°W., 30 lks., with down fir trunk, 24" diam., alongside, with scribe marks S5 visible on the bark and scribe marks OS R W BT visible on opened blaze. From this same point, the ¼ sec. cor. of sec. 33 only, T29S R4W bears N.87°43'25"E., 6.953 chs., hereinbefore described.