

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6359)

-----  
Set ¼ sec. post at proper distance, from which  
A Maple 12" dia., bears S.60°E., 16 lks. dist.  
A Maple 6" dia., bears N.80°E., 19 lks. dist.

-----  
GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 15 Page(s) 6407) (and Vol. 17 Pg. 7081)

-----  
Set a Laurel post 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. mkd. ¼ S on N. face, from which  
A Laurel 4" dia., bears N.55°W., 88 lks. dist. mkd. ¼S BT.  
A Laurel 4" dia., bears N.11°W., 30 lks. dist. mkd. ¼S BT.

-----  
Survey by Fredrick E. Warner - For: J.H. Baxter and Co. - March/April 1957 - C.S. File 42/257

-----  
Found iron pipe 1¼" dia., 10" above ground, firmly set, unmarked, from which  
A D.Fir 26" dia., bears N.21°30'W., 15.18 ft. mkd. ¼S33 RS 298 BT.  
A Madrona 10" dia., bears N.78°30'E., 21.12 ft. mkd. ¼ S33 RS 298 BT.  
I mkd. iron pipe RS 298 as true position of ¼ cor. to sec. 33

-----  
BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, and Robert Browning, Surveying Technician, under Group #1686, surveyed May 1993 thru April. 1995 - (DCSO records Vol. 52 Page(s) 20094-5)

-----  
The ¼ sec. cor. of sec. 33 only, restored by person(s) unknown, this position was used and perpetuated by Warner, in 1957, and is accepted as a careful and faithful determination of the original corner; monumented with an iron pipe, 1¼" diam., firmly set, projecting 10" above ground, from which bearing trees mkd. by Warner:  
A madrone, 14" diam., bears N. 79½° E., 31½ lks., with faint scribe marks BT visible on the bark.  
A fir, 33" diam., bears N. 22¼° W., 22½ lks., with healed blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, directly over the iron pipe, with brass cap mkd.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

T29S R4W  
¼ S 33  
T30S R4W  
1994

from which a new bearing tree  
A cedar, 10" diam., bears N.64°E., 45 lks., mkd. ¼ S33 BT.  
Deposit a white "DEEP-1" magnetic marker at base of stainless  
steel post.

Fd. Ok by Ken Hoffine, July 2005 - M148-23