

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6375)</p> <p>-----</p> <p>Set ¼ sec. post at average distance, from which A R.Fir 24" dia., bears N.30°W., 16 lks. dist. A R.Fir 24" dia., bears S.50°E., 13 lks. dist.</p>
<p>Survey by Jack L. Sheppard, LS #180 - For: Umpqua Plywood - Jan/Feb. 1955 - C.S. File 41/337 and M 3-68</p> <p>-----</p> <p>Set 1" iron pipe. (Proportioned) 20" Cedar S.53°E., 22.5 ft. scribed ¼ S33 LS 180 BT. 8" Fir N.22½°E., 48.9 ft. scribed ¼ S28 LS 180 BT.</p>
<p>Troy Rambo - For: Seneca Jones Timber Co - May 2003 - M142-32</p> <p>-----</p> <p>Found - 1" iron pipe Rotten Cedar stump with visible scribes, bears S.53°E., 22.5 ft. 22" DF with a healed face, bears N.22½°E., 48.9 ft.</p> <p>Scribed- ¼ S28 BT" on a 13" G.Fir, bears N.62°W., 5.1 ft. ¼ S33 BT" on a 10" DF, bears N.88°E., 16.4 ft. ¼ S33 BT" on a 15" DF, bears S.38°E., 16.4 ft. ¼ S33 BT" on a 8" DF, bears S.55°W., 27.9 ft.</p>
<p>Ken Hoffine - For: Lone Rock Timber Co. - July 2005 - M148-23</p> <p>-----</p> <p>Found - 1" iron pipe 22" D.Fir bears N.22°E., 49.1 ft. (rec. N.22½°E., 48.9 ft.) 10" D.Fir bears <u>S.84¼°E., 36.0 ft. (Rec. N.88°E.)</u> 16.4 ft. tag 36.0 ft.) visible scribing. 20" Rotten Cedar stump bears S.52½°E., 23.5 ft. (Rec. S.33°E., 22.5 ft.) visible scribing. 15" D.Fir bears S.29¾°E., 16.0 ft. (rec. S.38°E., 16.4 ft.) visible scribing and tag. 8" D.Fir bears S.52¾°W., 27.9 ft. (rec. S.55°W., 27.9 ft.) visible scribing and tag. 13" G.Fir bears N.59½°W., 5.1 ft. (rec. N.62°W., 5.1 ft. visible scribing and tag.</p> <p>Corner lies on NW facing slope approx. 75 ft. north of main ridge top & approx. 150 ft. South of new dirt road.</p>
<p>Fd. Ok by Ken Hoffine, Aug. 2008 - M156-54</p>
<p>1</p>