

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 340540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM survey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July/Oct 1977 (DCSO records Vol. 39 Page(s) 15903)

-----  
Point for the center ¼ sec. cor. of sec. 9, t intersection with the E. and W. center line.

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd: C ¼ S9  
1969

from which

A Fir 40" dia., bears S.8½°W., 109 lks. dist. mkd. C¼ S9 BT.

A Yew 13" dia., bears N.30½°W., 93 lks. dist. mkd. C¼ S9 BT.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-29 A/D

-----  
Found - 3¼" BLM brass cap on 2½" I.P. 1.0' above ground.  
47" Fir bears S.8°W. 73.5' (109 lks) healed blaze.

Set - 18" dead standing yew bears N.30°W. 59.5' (93 lks)  
20" Fir bears S.80°E. 25.7' to nail in right side center scribed "C1/4S9BT"

27" Fir bears S.66¾°W. 35.8' to nail in left side center scribed "C1/4S9BT"

New - Added nails (per mentioned locations) and LS washer 90216 to BTs.