

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6370)

Set ¼ sec. post, from which
A B.Oak 4" dia., bears S.85°E., 5 lks. dist.
A Laurel 4" dia., bears S.85°W., 16 lks. dist.

George J. Wenderoth - April 1957 - M 5-30

Location of corner determined by proportional measurement (halfway between section corners)
Set 1" Iron pipe, fro which
12" Fir S.0°35'E., 10.3 ft.
20" Fir N.70°W., 9.7 ft.

Fd. OK, Oct. 1992 by G. Lang - M 117-1

Ken Hoffine - For: Lone Rock Tbr Co. - July 2005 - M148-23

Set - 5/8"x40" iron rod with 2½" alum cap mkd: LONE ROCK TIMBER T29S R4W S33 S34 2005 PLS2291.
12" D.Fir bears S.18¾°E., 49.7 ft, we scribe ¼ S34 BT and tag tree
10" D.Fir bears S16¼°W., 19.5 ft, we scribe ¼ S33 BT and tag tree
28" existing D.Fir BT bears N.71°W., 18.2 ft, healed face we tag
10" D.Fir bears N.82¾°E., 57.8 ft., we scribe ¼ S34 BT and tag tree
1" iron pipe set by Pacific Tbr. Corp. in 1957 bears N.71¾°W., 7.98 feet
Set - 5/8" x 40" iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS2291 bears S.3¾°W., 58.62 ft
5/8" x 40" iron rod with yellow plastic cap marked LONE ROCK TIMBER PLS2291 bears S.88½°W., 69.93 ft.
Corner sets on west facing slope approximately 175 feet west of BLM road 30-4-3.1 road.

Fd. Ok by Ken Hoffine, Aug. 2008 - M156-54