

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec Cor for 27, 28, 33 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6370)

-----  
Set a post cor. of secs. 27, 28, 33 and 34, from which  
A Laurel 8" dia., bears N.2°W., 12 lks. dist.  
A Red Fir 28" dia., bears S.60°E., 25 lks. dist.  
A Red Fir 12" dia., bears N.60°E., 90 lks. dist.  
A Cedar 24" dia., bears S.47°W., 27 lks. dist.

Survey by Jack L. Sheppard, LS #180 - Jan/Feb. 1955 - C.S. File 41/337

-----  
Set 1" Iron pipe from original government BTs.  
32" Fir S.60°E., 16.5 ft. (Old BT)  
36" Fir N.60°E., 59.4 ft. (Old BT)  
44" Cedar S.47°W., 17.8 ft. (Old BT)  
12" W.Fir N.16°W., 27.0 ft. scribed S28 LS 180 BT.(New BT)

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-137

-----  
Found - 1" I.Pipe.  
36" Fir N.60°E., 59.4 ft., good scar.  
44" Cedar S.47°W., 17.8 ft., opened, scribing visible.  
12" W.Fir N.16°W., 27.0 ft., scribing visible.  
32" Fir S.60°E., 16.5 ft., snag.  
New BT - 12" Cedar S.85°E., 32.5 ft. "T29S R4W S34 CS BT"

Fd. OK, Oct. 1992 by G. Lang - M 117-1

Troy Rambo - For: Seneca Jones Timber Co - May 2003 - M142-32

-----  
Found - 1" iron pipe  
48" I.Cedar with healed face, bears S.47°W., 17.8 ft  
45" DF with healed face, bears N.60°E., 59.4 ft.  
Rotten G.Fir snag with a healed face, bears N.16°W., 27.0 ft.  
Rec 32" DF bearing S.60°E., 16.5 ft. now a low stump  
Scribed- "S27 BT" on 14" DF, bears N.44°E., 26.5 ft.  
"S34 BT" on 10" I.Cedar, bears S.85°E., 12.6 ft.

Fd. Ok by Ken Hoffine, July 2005 - M148-23

Fd. Ok by Ken Hoffine, Aug. 2008 - M156-54