

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6371)

Set a post cor. of secs. 21, 22, 27 and 28, from which
A B.Oak 10" dia., bears S.28°E., 45 lks. dist.
A B.Oak 12" dia., bears N.33°E., 62 lks. dist.
A B.Oak 6" dia., bears N.13°W., 33 lks. dist.
A B.Oak 4" dia., bears S.14°W., 18 lks. dist.

B. B. Irving, County Surveyor - Wit: A.R. Evans - March 1948 - M 13-69 & C.S. File 39/166 (added 1/21/2014)

Found - 2" x 2" madrona post, replaced with 3/4" iron pipe.
OBT, 66" Fir scribed S27 CS BT, S.37°44'E., 29.2 ft.
Remarked Madrona stump with illegible scribed marks,
S.57°12'W., 28.3 ft.
44" Fir S.38°E., 37.5 ft.
New BTs -14" Fir S.35°W., 22.6 ft.
40" D.Fir N.31½°W., 66.6 ft.
10" D.Fir N.70°E., 68.1 ft.

CS file shows a sketch of a 66" Fir & a laurel stump and has a note saying "Approx. Cor. pos. from facing of trees -"
Added 1/21/2014 by RWS & JC DCSO

Douglas Co. Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

Found 3/4" Iron pipe at corner and all BTs.
Scribed -12" W.Fir S.80°W., 25.0 ft. "S28 CS BT".

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15868)

The Sec. cor., perpetuated and recorded by Irving in 1948, from original evidence no longer in existence, and further perpetuated and recorded by Byron in 1956. This corner is accepted as the best available evidence of the original corner position, monumented with an iron pipe 3/4" dia., firmly set, projecting 8" above ground, from which a bearing tree described by Irving:

A Fir 48" dia., bears S.37¼°E., 61 lks. dist. with scribe marks S27 CS BT visible on bark blaze, and scribe marks T29S R4W S27 CS BT, by Irving in 1948, visible on bark blaze alongside.

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and bearing trees mkd. by Irving
A Fir 15" dia., bears N.70°E., 102 lks. with healed blaze.
A W.Fir 17" dia., bears S.35°W., 34 lks., with healed blaze.
A Fir 43" dia., bears N.30½°W., 102 lks., with healed blaze.
and a bearing tree mkd. by Byron
A W.Fir 17" dia., bears S.79½°W., 36 lks., with healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
directly over iron pipe, with brass cap mkd: T 29 S R 4 W
S 21 | S 22
S 28 | S 27
1969
Corner is located at SE. cor. of logged area, edges bear N.
and W.

Fd. Ok by K.Hoffine - 9/97 - M 128-12
Found OK by T. Rambo May 2003 - M142-32

James Klein - For: Williams/Pacific Connector Gas Pipeline
Project - 7/2015 - M166-44 A-F

Found - 3¼" brass cap stamped BLM 1969; Note: Monument is
incorrectly marked S27 is stamped West of S28.
25" Fir with tag dated 5/03; N.70°E., 67.3'.
46" Fir stump, S.37¼°E., 40.3'
22" W.Fir with healed face and tag dated 7/57,
S.35°W., 22.4'
52" Fir with healed face and tag dated 7/57,
N.30½°W., 67.3'