

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6373-74)

-----

Set a post corner of secs. 9, 10, 15 and 16, from which

- A B.Oak 16" dia., bears S.42°E., 40 lks. dist.
- A B.Oak 12" dia., bears N.80°E., 32 lks. dist.
- A W.Oak 10" dia., bears N.76°W., 52 lks. dist.
- A Laurel 6" dia., bears S.70°W., 60 lks. dist.

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6393)

-----

Witness trees all standing. Set new post.

Survey by John H. Markham, Jr. - For: Hult Lumber Co. - April/June 1964 - C.S. File 51/292 and M 28-25

-----

(Set by double proportional measurement)

Set 1" x 30" Iron pipe.

New BTs -12" Cedr bears S.35°E., 32.1 ft. mkd. S15 BT.  
 15" Fir bears S.20°W., 53.0 ft. mkd. S16 BT.  
 36" Fir bears N.10°W., 40.5 ft. mkd. S9 XX BT.  
 48" Laurel bears N.40°E., 38.2 ft. mkd. S10 T29S R4W BT.

All bearings to BTs were estimated since compass was lost.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15874)

The Sec. cor. at proportional distance; there is no remaining evidence of the original corner.

Set an iron post 28" long 2½" dia., 24" in the ground, with brass cap mkd:

T 29	S R 4 W
S 9	S 10
S 16	S 15
1969	

from which

- A Fir 6" dia., bears N.39°E., 27 lks. dist. mkd. T29S R4W S10 BT.
- A Chinquapin 6" dia., bears S.69½°E., 29½ lks. dist. mkd. T29S R4W S15 BT on bark.
- A Fir 34" dia., bears S.82°W., 53 lks. dist. mkd. T29S R4W S16 BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9, 10, 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Madrone 50" dia., bears N.22°W., 44 lks. dist. mkd. T29S R4W S9 BT.

From this point, a local corner established by Markham in 1964, bears S.83°52'W., 0.525 chs. dist., monumented with an iron pipe 1" dia., firmly set, projecting 10" above ground, from which bearing trees mkd. by Markham:

A Madrone 50" dia., bears N.37½°E., 58 lks. dist. with scribe marks S10 T29S R4W BT visible on bark.

A Cedar 13" dia., bears S.40°E., 49 lks. dist. with scribe marks S15 BT visible on open blaze.

A Fir 15" dia., bears S.20°W., 80 lks. dist. with illegible scribe marks visible on open blaze.

A Fir 42" dia., bears N.16°W., 61 lks. dist. with scribe marks S9 XX BT visible on bark blaze.

Fd. Ok by Lloyd Tolbert, May 2005 - M147-66

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2747, surveyed May/July 2014 - (DCSO records Vol. 58 page(s) 23201)

-----  
The cor. of secs. 9, 10, 15, & 16, monumented with an iron post, 2½" dia, firmly set, projecting 3" above ground, with brass cap (properly) mkd.

from which BTs mkd. by Roseberry and Jelley in 1967-77

A fir stump, 22" dia, bears N.39°E., 17.8 ft., with a healed blaze.

A chinquapin, 8" dia, bears S.69½°E., 19.5 ft., with a healed blaze.

A fir, 32" dia, bears S.82°W., 35.0 ft., with a healed blaze.

A madrone, 65" dia, bears N.22°W., 29.0 ft., with a healed blaze.

and a new bearing tree

A fir, 4" dia, bears N.10¾°E., 5.2 ft., mkd. X BT.

From this cor., a point established as the cor. of secs. 9, 10, 15, & 16, by Markham, in 1964, bears S.83°52'W., 34.6 ft., monumented with an iron pipe, 1" dia., grown into the N. side of a fir tree, and is not accepted as the cor. and not utilized in the course of this survey.

NAD 1983 (2011)

Latitude: 43°03'16.23"N Longitude: 123°10'17.51"W