

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6394)

Set an Oak post for the 1/4 sec. corner between secs. 9 and 10, from which

- A W.Oak 15" dia., bears S.81°W., 73 lks. dist.
- A Pine 15" dia., bears N.45°E., 7 lks. dist.

Claude Kerr - June 6, 1950 - C.S. File 40/252

The original Pine BT still there and scribe marks found. I put a new Cedar post in for corner and marked new BT:

- Red Fir 20", bears S.15°W., 40 lks. mkd. 1/4 S9 BT.
- The original BT, 32" Pine bears N.45°E., 6 lks. mkd. 1/4S.

John H. Markham, Jr. - For: Stomar Lumber Co. - Feb. 18, 1957 - C.S. File 42/248

Corner point determined by O.B.T.:

- A 48" Pine bears N.45°E., 4.6 ft., found scribe, O.B.T.
 - A 20" Fir bears S.17°W., 27.0 ft., O.B.T.
- At point for corner, SET 1 1/4" x 36" Iron pipe, 24" in ground, from which
- A 20" Fir bears S.26°E., 27.5 ft. mkd. 1/4 S10 BT.
 - A 20" Pine bears S.85°W., 40.8 ft. mkd. 1/4 S9 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-130

Found - 1 1/4" I.Pipe at corner and both BTs as recorded by Markham.
Rescribed 20" Pine S.85°W., 40.8 ft. scribed 1/4 S9 CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15876-77)

The 1/4 cor., perpetuated and recorded by Kerr in 1950, and further perpetuated and recorded by Markham in 1957, monumented with an iron pipe 1 1/4" dia., firmly set, projecting 14" above ground, from which the remains of the original bearing trees:

- A Pine 40" dia., bears N.45°E., 7 lks. dist. with scribe mark 4 visible on opened blaze.
- and a bearing tree mkd. by Kerr:
- A Red Fir 20" dia., bears S.15°W., 39 lks. dist. with healed blaze.
- (Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and bearing trees mkd. by Markham

A Fir 22" dia., bears S.26°E., 41 lks. dist. with healed blaze.

A Pine 23" dia., bears S.85°W., 61 lks. dist. rescribed by Byron in 1963, with scribe marks ¼ S9 CS BT visible on double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd: T 29 S R 4 W

¼
S 9 | S 10
1969

Fd. Ok by Lloyd Tolbert, May 2005 - M147-66