

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6394)

Set a Fir post for secs. 3, 4, 9 and 10, from which
A Fir 6" dia., bears N.36°E., 30 lks. dist.
A Laurel 8" dia., bears S.20°E., 7 lks. dist.
A Cedar 30" dia., bears S.42°W., 17 lks. dit.
A Laurel 8" dia., bears N.43°W., 40 lks. dist.

Claude Kerr - June 6, 1950 - C.S. File 40/252

Found scribe on Incense Cedar and the scar on the 6" Fir, now a 26" tree.
I SET a 4" x 4 ft. Cedar post and scribed S3 S4 S9 S10 on it.
I rescribed the small original BT on bark, "¼ S BT". This tree now is a Red Fir 26", bears N.36°E., 30 lks.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Dec. 2, 1959 - C.S. File 42/345-5

Sec. cor. as determined by Orig. BT:
30" Fir N.36°E., 19.8 ft., Orig. BT.
At corner point found scribed wood post.
Set 3/4" x 30" Iron pipe, from which
8" B.Oak N.73°E., 26.3 ft. S3 R4W BT.
20" Laurel N.10°E., 36.0 ft. S3 T29S R4W BT.
6" Laurel N.41°W., 25.8 ft. S4 T29S R4W BT.
9" Laurel S.9°E., 4.0 ft. S10 T29S R4W BT.
7" Fir S.20°E., 14.2 ft. X01SX BT.
Top of main ridge bears East 80.0 ft.
SW. corner sec. 4 bears N.87°35'W., 4180.0 ft.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15877-78)

The Sec. cor., perpetuated and recorded by Kerr in 1950, subsequently perpetuated by Markham in 1959, monumented with an iron pipe, 3/4" dia. firmly set, projecting 10" above ground, from which the remains of the original bearing trees
A Fir 29" dia., bears N.36°E., 30 lks. dist. with healed blaze, and rescribed by Kerr in 1950, with scribe marks X ¼ BT visible on bark blaze.
A shattered Cedar 36" dia., bears S.42°W., 17 lks. dist., no marks visible.
and bearing trees mkd. by Markham
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Madrone 22" dia., bears N.9½°E., 54½ lks. dist. with scribe marks S3 T29S R4W BT visible on bark.

A B.Oak 8" dia., bears N.72½°E., 43 lks. dist. with healed blaze.

A Madrone 11" dia., bears S.30¼°E., 7 lks. dist. with scribe marks S10 T29S R4W BT visible on bark.

A Fir 10" dia., bears S.26 ¾°E., 22 lks. dist. with healed blaze and scribe marks BT visible on bark.

A Madrone 8" dia., bears S.73 ¾°W., 35½ lks. dist. with illegible scribe marks visible on bark.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd: T 29 S R 4 W

S 4	S 3
S 9	S 10
1969	

from which a new bearing tree

A Fir 12" dia., bears N.11°W., 87½ lks. dist. mkd. T29S R4W S4 BT.

Fd. Ok by Lloyd Tolbert, May 2005 - M147-66

David Edwards - For: Roseburg Resources - 10/2024 - M184-31

Found - BLM brass cap

A 36" Fir bears N.38½°E., 19.8'

A 14" Dead Madrone bears S.73¾°W., 23.4'

A 25" Fir bears N.11°W., 57.8'

The firs have healed blaze.

5.5' steel post are set 2' N.10°E., on line and 2' N.82°W.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-29 A/D

Found - ¾" BLM brass cap on a ½" I.P. 0.4' above ground w/ an aluminum post alongside and a post 2' N. 38" Fir bears N.36°E. 19.8' with hacked "X BT" and tag by CM BM 6/23.

Dead, standing 11" Madrone bears S.73°W. 26.1' (35½ lks) with tag by CS 4/63.

28" Fir bears N.11°W. 57.7' with healed blaze and tag by AJG 7/28/69.

20" Fir stump 4.5' tall bears S.26¾°E. 14.5' (22 lks)

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Set -	22" Madrone stump 2' tall bears N.9½°E. 35.9' (54½ lks) 2' tall shattered cedar bears S.42°W. 11.2' (17 lks) burnt pieces lying around.
	24" Fir bears S.90°E. 96.1' to a nail in S. Face scribed "T29SR4WS10BT" w/ ls washer below. Tags by 80216 7/24/24.
	11" Fir bears S.68½°W. 27.0' to a nail in N. Face scribed "T29SR4WS9BT" w/ ls washer below. Tags by 90216 7/24/24.
Added -	Painted existing BTs, replaced tags and added nails to S.E. and E. Faces. Painted and tagged stumps and standing dead madrone. Added post W. 5' and N.10°E. 5' w/ boundary signs.