

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6395)

Set Hemlock post for the ¼ sec. cor., from which
A Laurel 10" dia., bears N.70°E., 9 lks. dist.
A Yew 8" dia., bears N.55°W., 10 lks. dist.

G.G. Stewart, Douglas Co. Surveyor - Wit: Frank Evans and C. Crocker - Feb. 3, 1922 - M 2-4

Found a decayed 10" Yew and a Laurel stump which were original BTs.
Set 5/8" Iron pipe from BTs with a 4" Fir marker., from which
Fir 16" dia., bears S.25°W., 22.5 ft.
Fir 12" dia., bears N.21°W., 23.5 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-119

Found - 1/2" I.Pipe at corner and both BTs as recorded by Stewart.
12" now 20" Fir N.21°W., 23.5 ft., shows good scar.
SW. BT, now down.
Set Brass cap alongside I.P. at cor. mkd:
County Surveyors Office
¼ S4 | S 3 T29S R4W
1963
New BT - 22" R.Fir bears S.3°E., 28.0 ft. scribed ¼ S3 CS BT.

Fd. OK, April 1993 by G. Lang - M 118-13

David Edwards - For: Roseburg Resources - 10/2024 - M184-31

Found - Brass cap
A 17" Yew bears N.55°W., 6.6'
A 34" Fir bears N.21°W., 23.5'
Fir with a healed blaze.
New BT - A 5" diam. Fir scribed "¼ S3 BT" bears S.9°E., 5.3'
A 5.5' steel post is set 2 ft S.10°W., on line.

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates Professional Land Surveyors - 2024 - M185-29 A/D

Found - 2½" Brass cap on a 1½" I.P. above ground

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 4

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

	Steel post bears S.10°E. 2'. 5" Fir bears S.9°E. 5.3' with scribe and tag "CM BM 6/23 David Edwards Land Surveying" 33" Fir stump bears N.24¼°W. 22.9' with healed blaze and tag "K MAC A THOMAS 11/10/54" 28" Fir stump bears S.3°E. 28.0' with mostly healed face.
Set -	7" Fir bears N.19½°E. 28.4' to a nail in E. face scribed "¼S4BT" w/ LS washer below tag on front and back by 90216 7/26/24.
tags	10" Maple bears S.41¼°W. 38.9' to a nail in N.W. face scribed "¼S4BT" w/ LS washer below on front and back by 90216 7/26/24. 2" Yew bears N.41¾°W. 4.5' to a nail in N.E. face scribed "¼S4BT" w/ LS washer below tags on front and back by 90216 7/26/24.
New -	Added post S.10°W. 5' and N.10°E. 5' Added tag, nail, and paint to the 5" Fir.