



PRIMARY CORNER DESCRIPTION Sec. Cor. for 3 & 4 only, T30-4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, with brass cap mkd.

T29S R4W  
 S 34  
 S 4 | S 3  
 C C  
 T30S R4W  
 1994

from which

A fir, 17" diam., bears S.42¼°E., 53 lks., mkd. T30S R4W S3 CC BT.

A fir, 18" diam., bears S.84½°W., 80 lks., mkd. T30S R4W S4 CC BT.

From this point, the original closing cor. of secs. 3 & 4, perpetuated by Markham, in 1951, further perpetuated by Ramsey, in 1959, further perpetuated by Byron, in 1963, bears N 0°19'57"W., 0.038 chs.; monumented with an iron pipe, 1¼" diam., firmly set, projecting 1" above ground, from which the remains of an original bearing tree:

A sawed fir stump, 36" diam., bears S.8°W., 27 lks., with no marks visible. (Record, 24 lks.)

and the remains of a bearing tree mkd. by Markham

A cedar, 27" diam., bears S.5°E., 48 lks., with healed double blazes.

and a bearing tree mkd. by Byron

A fir, 17" diam., bears S.55 3/4°W., 78 lks., with healed double blazes.

From this same point, the ¼ sec. cor. of sec. 34 only, T29S R4W bears S.88°52'15"E., 5.742 chs.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2777, surveyed June/July 2015/- (DCSO records Vol. 58 Page 23511-12)

The closing cor. of secs. 3 and 4, on the N. bdy. of the Tp., bears N.88°54'54"W., 379.30 ft., monumented with a stainless steel post, firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the BTs mkd. by Seibold and Browning in 1993-95

A fir, 21" dia., bears S.42¼°E., 35.0 ft., with a healed blaze.

A fir, 20" dia., bears S.84½°W., 52.8 ft., with a healed blaze.