

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6371)

-----  
Set ¼ sec. post at average distance, from which  
A W.Fir 30" dia., bears N.25°E., 54 lks. dist.  
A R.Fir 20" dia., bears S.25°E., 53 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

-----  
Corner set halfway between section corners.  
Set an iron pipe with brass cap at corner point mkd. "¼ S27 34 T29S R4W County Surveyors Office 1956"  
from which  
10" R.Fir bears N.45°E., 40.0 ft. mkd. ¼ S27 CS BT.  
12" R.Fir bears N.56°W., 27.0 ft. mkd. ¼ S27 CS BT.  
30" Cedar bears S.52°W., 35.5 ft. mkd. ¼ S34 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-141

-----  
Found - Brass cap.  
10" Fir N.45°E., 40.0 ft., OK.  
12" Fir N.56°W., 26.0 ft., OK.  
30" Cedar S.52°W., 35.5 ft., down.  
New BT - 5" Fir S.49°W., 25.8 ft. scribed ¼ S34 CS BT.

Fd. OK, Oct. 1992 by G. Lang - M 117-1  
Found OK by G. Nygren, Sept. 2001 - M137-22

James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F

-----  
Found - 2.5" brass cap, stamped County Surveyors Office 1956  
No BTs were found.  
New - 13" D.Fir (scribed ¼ S27 BT), set tag dated 11/13, N.10°E., 28.5' to nail side center.  
17" D.Fir (scribed ¼ S34 BT), set tag dated 11/13, S.18°W., 16.6' to nail side center.