

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6372)

Set ¼ sec. post at average distance, from which
A B.Oak 8" dia., bears S.75°E., 60 lks. dist.
A B.Oak 12" dia., bears N.37°W., 43 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

Corner set halfway between section corners.
Set an Iron pipe with brass cap mkd. "¼ S22 S27 T29S R4W
County Surveyors Office, 1956".
Scribed -20" Fir S.65°E., 35.5 ft. mkd. ¼ S27 CS BT T29S R4W
30" Fir N.10°W., 62.0 ft. mkd. ¼ S22 CS BT T29S R4W
30" Laurel, North 80 ft. mkd. ¼ S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-141

Found - Brass cap.
20" Fir S.65°E., 35.5 ft., OK.
30" Fir N.10°W., 62.0 ft., stump.
32" Laurel North 80 ft., down.
New BT - 23" Laurel bears N.37°W., 46.0 ft.

Found OK by G. Nygren, Sept. 2001 - M137-22