

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6373)

Set ¼ sec. post at average distance, from which
A R.Fir 24" dia., bears N.33°W., 63 lks. dist.
A R.Fir 10" dia., bears S.67°E., 82 lks. dist.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15872)

Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance based on record ties of the Hathorn survey of the claim lines; there is no remaining evidence of the original corner.

Set an iron post 28" long 2½" dia., 24" in the ground with brass cap mkd: T 29 S R 4 W

¼ $\frac{S 15}{S 22}$
1969

from which

A Fir 11" dia., bears N.69¼°W., 67½ lks. dist. mkd. ¼ S15 BT.

A Fir 20" dia., bears S.39¼°W., 4 lks. dist. mkd. ¼ S22 BT

From this point, an iron pipe, ½" dia., firmly set, projecting 6" above ground, bears S.84°30'W., 1.03 chs. dist.

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2747, surveyed May/July 2014 - (DCSO records Vol. 58 page(s) 23200)

The ¼ sec. cor. of secs. 15 & 22, monumented with an iron post, 2½" dia, firmly set, flush with ground, with brass cap (properly) mkd.

from which BTs mkd. by Roseberry and Jelley in 1967-77

A fir, 34" dia, bears S.39¼°W., 2.6 ft., with a healed blaze.

A fir, 20" dia, bears N.69¼°W., 44.6 ft., with a healed blaze.

Corner is located on the SE. side of a wood fencepost with wire fences extending N. and W.

From this cor., a point established by person(s) unknown bears S.84°30'W., 68.0 ft, monumented with an iron pipe, 1/2" dia., firmly set, projecting 6" above ground, and is not utilized in the course of this survey.