

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6374)

Set ¼ sec. post, at average distance, from which
An Alder 5" dia., bears N.15°E., 15 lks. dist.
An Alder 4" dia., bears S.32°E., 14 lks. dist.

Trees found standing in GLO survey by W.H. Byars, under Contract #376, dated Jan. 22, 1881 (DCSO records, Vol. 15 Page 6393)

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Aug/Dec. 1956 - C.S. File 42/188-6

Corner determined by old BT, a 10" Alder stump bears N.15°E., 10 ft.

Set a 2" x 30" steel shaft at corner point with 4" collar up.
From which

A 30" Fir bears S.36°W., 6.5 ft. mkd. ¼ S BT.

A 15" Maple bears N.44°W., 114.0 ft. mkd. ¼ S10 BT.

An 11" Fir bears S.47°W., 77.5 ft. mkd. ¼ S15 BT.

An 18" Cedar bears N.89°E., 113.0 ft. mkd. ¼ S10 BT.

Ben Branch Creek bears West 112.0 ft.

Road bears East 78.0 ft.

Corner lies in small side creek.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - April 1963 - C.S. File 52/126

Found - All new BTs as recorded by Markham, except NW. and 30" Fir to SW. are now stumps.

Do not find I.P. set at corner, which now falls in old cat road.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 4 W

¼ S 10

S 15

1963

New BT - 6" Fir bears S.49°W., 48.0 ft. scribed ¼ S15 CSBT.

Cor. Fd. and tied in BLM resurvey by Roseberry and Jelley, under Group #'s 255; 701; and 938 - Surveyed July 1967/Oct. 1977 (DCSO records, Vol. 39 page 15875)

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2747, surveyed May/July 2014 - (DCSO records Vol. 58 page(s) 23202)

The ¼ sec. cor. of secs. 10 & 15, monumented with an iron post, 1¼" dia, firmly set, projecting 15" above ground, with brass cap (properly) mkd.

from which the remains of a BT mkd. by Byron, in 1963

A fir snag, 22" dia, bears S.49¼°W., 48.2 ft., with no marks visible.

and new bearing trees

A fir, 5" dia, bears S.62½°W., 30.7 ft., mkd. X BT.

A fir, 8" dia, bears N.10½°W., 37.9 ft., mkd. T29S R4W S10 BT.