

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6394)

Set Laurel post for the 1/4 sec. cor. between secs. 3 and 10, from which

A Laurel 36" dia., bears North, 6 lks. dist.

A Cedar 10" dia., bears S.45°W., 11 lks. dist.

Claude Kerr - June 6, 1950 - C.S. File 40/252

Found both the original BTs. Scribe of 1/4 S on the 36" Laurel. I reset the corner by putting in a 4" x 4 ft. Cedar post scribed 1/4 S on E. and W. sides, S3 on North side, and S10 on South side.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-128

Found - Squared Cedar stake on ground at corner.
Both orig. BTs. Orig. 36" now 42" Laurel, North 40.1 ft., shows scribe.
Orig. 10" now 30" Cedar S.45°W., 7.3 ft. shows good scar.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 4 W

1/4 S 3

S 10

1963

Rescribe 42" Laurel, North, 6.0 ft. 1/4 S3 CS BT.

Fd. Ok by Lloyd Tolbert, May 2005 - M147-66