

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6366)

Set ¼ sec. post, from which
A B.Oak 10" dia., bears S.13°E., 33 lks. dist.
A B.Oak 8" dia., bears N.27°W., 63 lks. dist.

Douglas County Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

Corner set halfway between section corners.
Set an Iron pipe with brass cap at corner point mkd. "¼ S34 S35 County Surveyors Office, 1956", from which
10" W.Fir bears N.46°W., 54.5 ft. mkd. ¼ S34 CS BT.
8" W.Fir bears S.21°E., 93.0 ft. mkd. ¼ S CS BT.

Survey by Greg Lang, LS #2295 - For: Silver Butte Timber Co. - Oct. 1992 - M 117-1

Found - Brass cap.
18" W.Fir N.46°W., 54.5 ft.
Rotted stump, approx. S.21°E., 93.0 ft.
New BT - 6" Fir N.24°E., 8.2 ft. scribed ¼ S34 BT.