

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6367)

-----  
Set ¼ sec. post, from which  
A Red Fir 10" dia., bears S.35°E., 54 lks. dist.  
A B.Oak 12" dia., bears S.35°W., 63 lks. dist.

Douglas Co. Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

-----  
Corner set halfway between section corners.  
Set an Iron pipe with brass cap at corner point mkd. "¼ S27|S26 T29S R4W County Surveyors Office 1956".  
Scribed -30" Fir N.43°E., 25.8 ft. mkd. ¼ S26 CS BT T29S R4W  
28" Fir N.63°W., 61.0 ft. mkd. ¼ S27 CS BT T29S R4W  
30" Laurel S.74°W., 10.0 ft. mkd. ¼ S CS BT.

Found OK by G. Nygren, Sept. 2001 - M137-22