

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec Cor for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6367)

Set a post cor. of secs. 22, 23, 26 and 27, from which
A Red Fir 18" dia., bears S.28°E., 45 lks. dist.
A Red Fir 12" dia., bears S.68°W., 33 lks. dist.
A Red Fir 10" dia., bears N.39°E., 49 lks. dist.
A Laurel 14" dia., bears N.49°W., 62 lks. dist.

Douglas County Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

Corner set by double proportional measurement.
Set iron pipe with brass cap at corner point mkd. "22 23 27 26 County Surveyors office 1956."
Scribed 4 trees:
24" Fir S.25½°W., 40.3 ft. mkd. S27 CS BT T29S R4W.
30" Laurel S.55°E., 72.7 ft. mkd. S26 CS BT T29S R4W.
30" Pine N.74°E., 40.5 ft. mkd. S23 CS BT T29S R4W.
8" Laurel N.29°W., 21.3 ft. mkd. S22 CS BT T29S R4W.
(Notation on RM 1-8 says "Bearings and distances revised")

Per notation on typed renewal in old records, "Reset brass cap S.17°W., 9.25 ft. Oct. 1959. L.L."

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - May 1963 - C.S. File 52/126-140

Found - Brass cap at corner and all BTs except NW BT.
New BT - 20" R.Fir bears N.89°W., 65.9 ft. scribed S22 T29S R4W CS BT.

Fd. Ok by K.Hoffine - 9/97 - M 128-12