

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6368)

-----  
Set a post cor. of secs. 14, 15, 22 and 23, from which  
A Red Fir 24" dia., bears S.45°W., 32 lks. dist.  
A Pine 24" dia., bears N.35°W., 66 lks. dist.  
A W.Oak 8" dia., bears S.60°E., 109 lks. dist.  
A W.Oak 6" dia., bears N.5°E., 35 lks. dist.

G.G. Stewart, Douglas Co. Surveyor - Wit: Frank Evans; C. Crocker - Feb. 3, 1922 - Vol. 3 Page 102

-----  
Original corner destroyed. Stumps of two old witness trees found. Set new corner, a 1" iron pipe, from which  
36" Bull Pine N.45°E., 143 lks.  
6" Laurel S.85°E., 28 lks.  
10" Laurel N.56½°W., 141 lks.  
36" Fir stump S.47½°W., 32½ lks. (Orig. BT)

N.E. Richardson, Deputy Co. Surveyor - Wit: E.S. Woodford - May 1945 - (No record source found)

-----  
Renewed from old BTs and marked the following trees:  
An 8" Laurel S.38°45'E., 26.0 ft.  
A 12" Fir N.68°00'E., 22.9 ft.  
No other trees near.

Douglas Co. Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

-----  
Found - 1" Iron pipe at corner.  
12" Fir bears N.62°E., 23.5 ft.  
8" Laurel S.44°30'E., 26.0 ft., mostly grown over.  
Old stump, S.43°W., 22.0 ft. no scribing left, may be original BT.  
Blaze and scribe new tree:  
12" R.Fir N.22°W., 91.0 ft. mkd. S15 CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15871-72)

-----  
The Sec. cor., perpetuated and recorded by Stewart in 1922, monumented with an iron pipe 1" dia., firmly set, projecting 2" above ground, from which the remains of the original bearing trees:

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 14, 15, 22 and 23

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A root hole bears S.45°W., 32 lks.  
A root hole bears N.35°W., 66 lks.  
and the remains of a bearing tree mkd. by Stewart  
A burned and decayed Pine stump, size indeterminate, bears  
N.45°E., 145 lks., no marks visible.  
and bearing trees mkd. by Richardson in 1945  
A Fir 18" dia., bears N.66°E., 35½ lks., with healed blaze  
A Madrone 15" dia., bears S.39°E., 40 lks no marks visible  
and a bearing tree mkd. by Byron in 1956  
A Fir 20" dia., bears N.17¼°W., 138 lks. with healed blaze  
At the corner point  
Set an iron post, 28" long, 2½" dia., 24" in the ground,  
directly over iron pipe, with brass cap mkd: T 29 S R 4 W  
S 15 | S 14  
S 22 | S 23  
1969  
from which a new bearing tree  
A Cedar 6" dia., bears S.55°W., 143 lks., mkd. T29S R4W  
S22 BT.

Kristian DeGroot - For: Bradford Lavanway - May 2013 - C.S.  
File 65/78-42

-----  
Found - USBLM BCIP per DCSO Vol.39 Pages 15871-72  
NAD 83  
43°02'23.87432"N. 123°09'10.06162"W.

BLM resurvey by George M. Winter, Cadastral Surveyor, under  
Group No. 2747, surveyed May/July 2014 - (DCSO records Vol.  
58 page(s) 23197)

-----  
The cor. of secs. 14, 15, 22, & 23, monumented with an iron  
post, 2½" dia., firmly set, projecting 3" above ground, with  
brass cap (properly) mkd.  
from which a BT mkd. by Richardson, in 1945  
A madrone, 28" dia, bears S.39°E., 26.4 ft., with a healed  
blaze.  
and a BT mkd. by Byron, in 1956  
A fir, 33" dia, bears N.17¼°W., 91.1 ft., with a healed  
blaze.  
and a new bearing tree  
A fir, 5" dia, bears S.57½°W., 9.7 ft., mkd. X BT.  
From the corner  
E., 2 ft., to the cor. of fences extending N., E., and S.