

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6369)

Set ¼ sec. post, from which
A B.Oak 7" dia., bears N.10°W., 25 lks. dist.
A B.Oak 15" dia., bears N.55°E., 77 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm Stoffel crew - April 1963 - C.S. File 52/126-111

Found - Orig. 7" now down and mostly rotted B.Oak, N.10°E., 16.5 ft., shows what I believe to be faint reverse scribe marks.

Remains of large Oak that checks for NE. BT.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 4 W
¼ S15 | S14
1963

New BTs -9" Cedar bears N.56°W., 10.5 ft. scribed ¼ S15 CS BT
14" R.Fir bears S.16°E., 23.6 ft. scribed ¼ S14 CS BT.

We find 10" Laurel that bears N.5°W., 4.0 ft. shows what appears to be bark scribing "R 32".

BLM resurvey by George M. Winter, Cadastral Surveyor, under Group No. 2747, surveyed May/July 2014 - (DCSO records Vol. 58 page(s) 23198)

The ¼ sec. cor. of secs. 14 & 15, perpetuated by Byron, in 1963, from original evidence no longer in existence, monumented with an iron post, 1¼" dia, firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which new bearing trees

A fir, 5" dia, bears S.46¼°W., 7.9 ft., mkd. X BT.

A fir, 6" dia, bears N.76½°W., 5.7 ft., mkd. X BT.

Search was made for the bearing trees established by Byron and none were recovered.

Corner is located on the W. side of an 8 ft. high field fence extending N. and S.