

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. H. Byars, Deputy Surveyor, under Contract #376, dated Jan. 22, 1881 - (DCSO records Vol. 15 Page(s) 6391-92)

-----  
Set ¼ sec. cor. A Fir post, from which  
A Cedar 20" dia., bears N.75°E., 48 lks. dist.  
A Fir 30" dia., bears S.70°W., 9 lks. dist.

Survey by William Ruppert, LS #866 - For: Richard Schalllich -May/June 1983 - C.S. File 58/270 and M 94-61

-----  
I cut open stumps in the vicinity of the proportioned ¼ corner, but I was unable to find any evidence.  
Set at proportional distance between section corners, 1" galv. Iron pipe 30" long, with 2½" brass cap mkd: "T29S R4W 1/4 S10 S11 LS 866 1983"  
Set 5 ft. steel fence posts with bearing tree signs attached:  
N.73°20'E., 1.2 ft. and  
S.73°20'W., 6.05 ft.  
No suitable bearing trees available.  
Original distances per GLO plat August 11, 1881.

BLM dependent resurvey by Wayne L. Rogers, Dale T. Bedell, Bryan S. Seibold, Cadastral Surveyors & Robert H. Browning, Surveying Technician, under Group #1625 surveyed Sept. 1991 thru April 1993 - (DCSO records Vol. 52 Page(s) 19786)

-----  
From the ¼ sec. cor. of secs. 10 & 11, reestablished at proportionate position by Ruppert, in 1983. There is no remaining evidence of the original corner, and because of the close agreement of this survey with Ruppert's record and error closures, this position is accepted as the corner; monumented with a galvanized iron post, 1" diam., firmly set, projecting 10" above ground, with properly marked brass cap from which new bearing trees  
A fir, 6" diam., bears N.50°E., 19 lks., mkd. ¼ S11 BT.  
A fir, 5" diam., bears N.40°W., 26 lks., mkd. ¼ S10 BT.

Found OK by R. Ward, Jan. 2002 - M139-35