

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, Contract #44 dated May 30, 1854
(DCSO records Vol. 13 Pg. 5607-5608)

-
- Set a post at proper distance from which:
- A Dogwood, 5" dia. bears S.58°E., 10 lks. dist.
 - A R.Fir, 6" dia. bears N.45°E., 24 lks. dist.
 - A Laurel, 4" dia. bears N.10°W., 28 lks. dist.
 - A Laurel, 12" dia. bears S.35°W., 22 lks. dist.

South Boundary of T.28-4, surveyed by W.H. Byars, contract #376 dated Jan. 22, 1881. (DCSO rec. Vol. 13 Pg. 5614)

-
- Set Cedar post for Sec. cor. from which:
- A Fir, 12" dia. bears N.40°E., 51 lks. dist.
 - A Cedar, 8" dia. bears S.80°E., 25 lks. dist.
 - A Fir, 14" dia. bears S.60°W., 42 lks. dist.
 - A Yew, 8" dia. bears N.54°W., 31 lks. dist.
- Note: Per note in Byars 1881 survey "In the execution of this work I found that the old line established for the S bdy of this Township was glaringly at fault..." Byars set his own corners See CS 63/166 BLM opinion file T28-4 (added 4/7/2010)

Irving Zirpel Jr. & William W. Glenn. B.L.M Dependent Resurvey dated August 29, 1957. (DCSO rec. Vol. 29 Pg. 12228)

-
- Found - A Fir turnout, 20" dia. bears N.40°E., 51 lks dist. no scribe marks visible.
- A Cedar snag, 17" dia. bears S.80°E., 25 lks. dist. with healed blaze.
 - A Fir snag, 21" dia. bears S.60°W., 42 lks. dist. with scribe mks. T2 3 visible on opened blaze.

Set an iron post at corner point with brass cap mkd:

T28S R4W
S 34 | S 35
S 3 | S 2
T29S 1958

- New BTs- A W.Fir, 13" dia. bears N.30°E., 12 lks. dist. mkd. T28S R4W S35 BT.
- A Cedar, 21" dia. bears S.35°E., 95 lks. dist. mkd. T29S R4W S2 BT.
 - A Cedar, 11" dia. bears S.80½°W., 55 lks. dist. mkd. T29S R4W S3 BT.
 - A Fir, 15" dia. bears N.66½°W., 65 lks. dist. mkd. T28S R4W S34 BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3; 34 & 35 T28-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bruce Shaner for Longview Fibre Co. 10/81 - 1/82 RM 3-54.

Found - Brass Cap, properly mkd. (set in 1958 resurvey)
20" W.Fir w/healed over face, bears N.30°E., 7.9'
20" Cedar BT, down, scribes vis., bears S.35°E.,
62.7'
24" cedar BT w/healed over face bears S.80½°E.,
37.3' (rec. 36.3')
18" D.Fir BT w/healed over face bears N.66½°W. 42.9'
18" Cedar, now down, no marks vis., bears S.80°E.,
16.5' (original BT)
22" Fir snag w/scribes vis., bears S.60°W., 27.7'
(original BT)
Note: N.E. original BT rotted & scattered in general
area.
New BT - A Cedar, 8" dia. bears S.27°E., 52.0' mkd. T29S R4W
S2 BT.

BLM resurvey by George M. Winter, Cadastral Surveyor, under
Group No. 2747, surveyed May/July 2014 - (DCSO records Vol.
58 page(s) 23194-5)

The cor. of secs. 2, 3, 34, & 35, on the N. bdy. of the Tp.,
perpetuated by Shaner, in 1981-82, monumented with an iron
post, 2½" dia, firmly set, flush with ground, with brass cap
(properly) mkd.
from which the remains of an original bearing tree
A fir snag, 14" dia, bears S.60°W., 27.7 ft., with
fragmentary scribe marks visible.
and the remains of BTs mkd. by Zirpel, Jr. and Glenn in 1957
A fir, 25" dia, bears N.30°E., 7.9 ft., with a healed
blaze.
A cedar, 34" dia, bears S.80½°W., 37.3 ft. with a healed
blaze. (Record, 36.3 ft.)
A fir stump, 29" dia, bears N.66½°W., 42.9 ft., with no
marks visible.
and a bearing tree mkd. by Shaner
A hemlock, 13" dia, bears S.26¼°E., 52.0 ft., with a
healed blaze. (County record, cedar)
and a new bearing tree
A fir, 11" dia, bears N.67½°W., 13.4 ft., mkd. T28S R4W
S34 BT.

NAD 1983 (2011)
Latitude: 43°05'03.30" N Longitude: 123°08'55.04"W

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Cor. Secs 2, 3; 34 & 35 T28-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM survey by Scott Toldness - PLS 90216 - Glahe & Associates
Professional Land Surveyors - 2024 - M185-29 A/D

-
- Found - 3¼" BLM brass cap on a 2½" I.P flush with ground.
14" Fir snag bears S.60°W. 27.7' with old scribe & blaze.
29" Fir snag bears N.29½°E. 7.9' healed blaze & K-tag.
41" Cedar bears S.81½°W. (S.80½°W.) 37.3' healed blaze & illegible BT tag.
29" Fir stump bears N.66½°W. 42.9' illegible tags.
15" dead red cedar bears S.26½°E (S.27°E.) 52.0' healed blaze and BT tag.
11" dead and down fir bears N.67½°W. 13.4' semi healed blaze and BT tag.
- Set - 32" Fir bears S.82½°E. 6.9' ro nail in left side center. Scribed "T29SR4WS2BT" with BT tag LS washer 90216 and mag nail at bottom of scribe.
27" Fir bears N.87°W. 35.3' to a nail in left side center, scribed "T28SR4WS34BT" with BT tag, LS washer 90216 and mag nail at bottom of scribe painted BTs and added distance to existing BTs.