

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6360)

Set ¼ sec. post at proper distance, from which
A Laurel 18" dia., bears N.2°E., 35 lks. dist.
A B.Oak 6" dia., bears S.60°W., 40 lks. dist.

GL0 survey by Wm. Thiel, Deputy Surveyor, under Contract #535, dated Feb. 5, 1889 (DCSO records Vol. 15 Page(s) 6402)

A post is standing in place mkd: ¼S probably set by Deputy Byars in 1872. I replace the same by a Maple post, 3 ft. long, 3" sq., 24" in the ground, mkd. ¼S on N. face, from which
A Fir 10" dia., bears N.7°E., 22 lks. dist. mkd. ¼ S BT.
A Pine 36" dia., bears S.4½°W., 25 lks. dist. mkd. ¼S BT
The Laurel mentioned in field notes of original survey is still standing but killed by fire, the letters showing plainly; the B.Oak is entirely destroyed.

Fd. and tied in GL0 survey by Wm. Thiel under Contract #535 dated Feb. 5, 1889 (DCSO records, Vol. 17 Pages 7054-55)

F.C. Frear, Deputy Co. Surveyor - Wit: Marrison; Safely; H. Wilson; C.J. Wilson - Oct/Nov. 1918 - C.S. File 7/18; M 1-3; Vol. 3 Pgs. 29-30 and Field book 14=45

Renew from old bearing trees. Set in 1½" x 30" Iron pipe, from which
Old government BTs bear as given. Remarked.

Survey by John H. Markham, Jr. - Wit: Dennis Vaughn and Geo. Vaughn - Nov. 2, 1951 - C.S. File 40/386-9

Determined by O.B.T., A Fir stump bears N.7°E., 14½ ft. dist. At corner point, Set 1" x 30" I.P., from which
A Cedar 14" dia., bears N.30°W., 20.0 ft. mkd. ¼ S35 BT.
A Fir 12" dia., bears N.57°E., 61.0 ft. mkd. ¼ S BT.
Section corner for 2 & 3 bears West, 165.0 ft.
There is a fence running approx. North and West from ¼ Cor.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-125

Found - 1" I.Pipe at corner.
14" Cedar N.30°W., 20.0 ft., now down.
12" Fir N.57°E., 61.0 ft., now stump.
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs -20" Cedar N.42°W., 28.8 ft. scribed ¼ S35 CS BT. 7" W.Oak N.57°W., 32.4 ft. scribed ¼ S35 CS BT.
Fd. OK by Ron Quimby, March 1996 - M 123-58 Fd. Ok by David Edwards - Jan 2005 - M 147-18 Fd. as per record 10/2023 D. Edwards - M182-80