

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6366)

-----  
Set ¼ sec. post at average dist., from which  
A B.Oak 8" dia., bears S.68°W., 15 lks. dist.  
A B.Oak 14" dia., bears N.67°E., 81 lks. dist.

Douglas County Surveyors Office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8

-----  
Corner set halfway between section corners.  
Set an Iron pipe with brass cap at corner point mkd. ¼ S 26 35 T29S R4W County Surveyors Office 1956.  
Bark scribed two trees:  
30" R.Fir North 23.0 ft. mkd. ¼ S26 CS BT T29S R4W.  
40" R.Fir S.33°30'E., 19.8 ft. mkd. ¼ S35 CS BT T29S R4W.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-126

-----  
Found - Brass cap at corner.  
North BT, now stump.  
40" Fir S.53°E., 19.8 ft. not S.33°E., 19.8 ft. snag  
New BTs -18" Fir N.77°E., 93.5 ft. scribed ¼ S26 CS BT.  
4" Fir S.32°W., 20.3 ft. scribed ¼ S36 CS BT.

David Edwards - For: Seneca Jones Timber Co. & Roseburg Resources Co. - Jan 2005 - M 147-18

-----  
Found - DCS brass cap  
40" Fir stump S.53°E., 19.8'  
11" Fir S.32°W., 20.3 H.B.  
Set - 6' steel post 2' south.

James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F

-----  
Found - 2½" brass cap stamped County Surveyors Office 1956  
13" Fir with healed face, S.32°W., 20.3'  
New - 6" W.Fir (scribed X BT) and tag dated 6/14, N.34°E., 6.3' to nail side center.