

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 540240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Survey by John H. Markham, Jr. - For: Stomar Lumber Co. - Aug/Dec. 1956 - C.S. File 42/188-3</p> <p>-----</p> <p>At corner point Set 3/4" x 30" Iron rod, from which A 10" W.Fir bears West, 44.0 ft. mkd. C ¼ S26 2880 BT. A 12" Fir bears N.7°E., 21.4 ft. mkd. C ¼ S26 BT. A 48" Fir bears S.81°E., 23.4 ft. mkd. C ¼ S BT on bark. Road bears West 23.0 ft. Creek bears South 40.0 ft.</p>
<p>Gerald Nygren - for: Silver Butte Timber Co. - Sept. 2001 - M 137-22</p> <p>-----</p> <p>Found - 3/4" iron rod per C.S. File 42/188. (Orig. BT) 48" Fir blow down, stump hole bears S.81°E., 23.4' Scribed- 8" D.Fir, N.8°W., 9.0' 15" Cedar, S.44°E., 13.5'</p>
<p>James Klein - For: Williams/Pacific Connector Gas Pipeline Project - 7/2015 - M166-44 A-F</p> <p>-----</p> <p>Found - 3/4" iron rod with no cap 10" fir with healed face and tag dated 8/01, N.18°E., 5.8' to nail side center. Note: this tree does not match bearing and distance per survey No. M137-22. 19" Cedar with healed face and tag dated 8/01, S.44°E., 13.51' to nail side center.</p>
<p> </p>