

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6367)  
-----  
Set ¼ sec. post at average distance, from which  
    A Red Fir 30" dia., bears S.28°E., 33 lks. dist.  
    A Red Fir 10" dia., bears N.46°W., 27 lks. dist.

Douglas County Surveyors office - James W. Byron, Deputy - May 1956 - C.S. File 47/101 and RM 1-8  
-----  
Corner set halfway between section corners.  
Set an Iron pipe with brass cap mkd. "County Surveyors Office ¼ S 23 26 T29S R4W 1956".  
Scribed -6" Fir N.5°E., 27.0 ft. mkd. ¼ S23 CS BT.  
          24" Laurel S.4°E., 16.3 ft. mkd. ¼ S26 CS BT T29S R4W.

Dan Saily, Lone Rock Timber Co. - Crew: Brett Ragon, Ignacio Roman & Trevor Clemo - 12/2023 - M183-28  
-----  
Found - Douglas Co. Surveyor's brass cap.  
New - 10" I.Cedar bears S.20°E., 15.0 ft  
      17" D.Fir bears S.47¾°W., 21.4 ft.  
      15" I.Cedar bears N.26½°W., 25.4 ft.  
      20" I.Cedar bears N.16½°E., 27.4 ft.  
No remaining evidence of 1956 Byron BTs. Corner lies on west facing slope approximately 150 feet east of wide draw running south, in mixed timber. Top of corner monument is 1.1 ft above ground level.