

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6361)

Set ¼ sec. post, from which
A Red Fir 12" dia., bears S.70°E., 17 lks. dist.
A Red Fir 4" dia., bears S.87°W., 21 lks. dist.

Survey by John H. Markham, Jr. - For: Stomar Lumber Co. -
Wit: Geo. Vaughn - C.S. File 40/386-8

Determined by O.B.T.
A 12" Fir bears S.87°W., 14.0 ft. (OBT) Found scribe.
A 24" Fir, windfall, bears S.70°E., 11.0 ft. (OBT)
At corner point Set 1" x 30" Iron pipe, from which
A 16" Cedar bears S.39°W., 17.2 ft. mkd. ¼ S35 BT.
A 30" Sugar Pine bears S.23°W., 45.5 ft. mkd. ¼ S BT.
A 12" Cedar bears N.35°E., 77.2 ft. mkd. ¼ S36 BT.
Creek bears East approx. 210 ft.
Creek bears South approx. 380 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike
Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-125

Found - 1" I.P.
16", now Cedar snag, S.59°W., 17.2 ft.
30" Sugar Pine S.23°W., 45.5 ft., now stump.
12" Cedar N.35°E., 77.2 ft., stump.
New BTs -7" Cedar S.44°E., 29.2 ft. scribed ¼ S36 CS BT.
12" Cedar N.12°W., 34.2 ft. scribed ¼ S35 CS BT.

Found OK by R. Rice, June 2003 - M142-46
Fd. Ok by David Edwards - Jan 2005 - M 147-18