

PRIMARY CORNER DESCRIPTION Sec Cor for 25, 26, 35 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6361-62)

-----  
Set a post cor. of secs. 25, 26, 35 and 36, from which  
A Laurel 14" dia., bears S.15°E., 13 lks. dist.  
A Laurel 18" dia., bears N.35°E., 62 lks. dist.  
A Laurel 10" dia., bears N.70°W., 15 lks. dist.  
A Laurel 12" dia., bears S.2°W., 34 lks. dist.

Douglas Co. Surveyors Office - Arthur R. Evans, Deputy - Crew - F.D. Smith; Harvey Potter; Ivan Taylor - May 1949 - C.S. File 43/94; Vol. 5 Pg. 17 and M 1-31

-----  
Found - 4" x 4" Cedar stake rotted and on ground and OBT's standing and dead:

14" Laurel S.15°E., 13 lks.  
18" Laurel N.35°E., 62 lks.  
10" Laurel N.70°W., 15 lks.

Drive 1¼" x 30" Galv. I.P. for corner.  
Marked new BTs

30" Fir S.61 3/4°W., 36.0 ft. mkd. T29S R4W S35 CSBT  
12" Fir N.8½°W., 46.0 ft. mkd. T29S R4W S26 CS BT.  
22" Cedar S.30°E., 20.1 ft. mkd. T29S R4W S36 CS BT.  
12" Fir N.27½°E., 55.5 ft. mkd. T29S R4W S25 CS BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-127

-----  
Found - 1¼" I.P. at corner.

22" Cedar S.30°E., 20.1 ft. OK.  
30" Fir S.61°W., 36.0 ft. OK.  
12" Fir N.8°W., 46.0 ft., stump.  
12" Fir N.27°E., 55.5 ft., stump.

New BTs -9" Laurel S.77°W., 51.6 ft. scribed S35 T29S R4W CS BT.

9" R.Fir N.45°W., 11.6 ft. scribed S26 CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15857-58)

-----  
The sec. cor. perpetuated and recorded by Evans in 1949, monumented with an iron pipe 1¼" dia., firmly set, projecting 8" above ground, from which the remains of the original bearing trees:

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec Cor for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

A Madrone snag 26" dia., bears N.35°E., 62 lks. dist., no marks visible on decayed blaze.  
 A Madrone snag 20" dia., bears S.15°E., 13 lks. dist., no marks visible on decayed blaze.  
 A Madrone root crown, size indeterminate, bears N.70°W., 15 lks. dist., no marks visible.  
 and the remains of bearing trees mkd. by Evans  
 A sawed Fir stump 12" dia., bears N.27°E., 85 lks. dist., no marks visible.  
 A Cedar 24" dia., bears S.31¼°E., 31 lks. dist. with scribe marks T29S S36 CS BT visible on partially healed blaze.  
 A Fir 30" dia., bears S.61¼°W., 54½ lks. dist., with scribe marks T29S R4W S35 BT visible on bark blaze.  
 A sawed Fir stump 14" dia., bears N.8½°W., 71 lks. dist., no marks visible.  
 and bearing trees mkd. by Byron in 1963  
 A Madrone 9" dia., bears S.75 3/4°W., 78½ lks. dist. with scribe marks S35 T29S R4W CS BT visible on partially healed blaze.  
 A Fir 10" dia., bears N.46 3/4°W., 17 lks. dist., with scribe marks S26 CS BT visible on partially healed blaze.  
 At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29	S R 4 W
S 26	S 25
S 35	S 36
1967	

from which a new bearing tree  
 A Fir 10" dia., bears N.19°E., 30½ lks. dist. mkd. T29S R4W S25 BT.

Found OK by R. Rice, June 2003 - M142-46

David Edwards - For: Seneca Jones Timber Co. - 11/2009 - M160-11  
 -----  
 Found - Brass cap  
           M1-31 BT: 30" dia., Fir brs. S.61¼°W., 36.0' cedar S.30°E., is dead.  
           An 18" dia., Fir w/2003 tag brs. N.19°E., 24.2'  
           An 18" dia., Fir W/1963 tag bears N.45°W., 11.6'  
 Set - Steel fencepost 2' N.79°E.

continued next page

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec Cor for 25, 26, 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

James Klein - For: Williams/Pacific Connector Gas Pipeline  
Project - 7/2015 - M166-44 A-F

-----  
Found - 3¼" brass cap stamped BLM 1967  
26.5" fir with healed face & tag dated 5/03,  
N.19°E., 24.8'  
21" madrone snag with tag dated 5/08, S.61°15'W.,  
36.0'  
24" fir with healed face & tag dated 4/63, N.45°W.,  
11.6'

Michael Erickson & Leonides Sadoval - For: Ensite USA -  
4/2019 - M171-67A

-----  
Found - 3¼" brass cap stamped BLM 1967  
26.5" fir with healed face & tag dated 5/03,  
N.19°E., 24.8'  
21" madrone snag with tag dated 5/03 S.15°E., 8.6'  
37" fir with tag dated 5/08, S.61°15'W., 36.0'  
24" fir with healed face & tag dated 4/63, N.45°W.,  
11.6'