

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6362)

Set ¼ sec. post, from which
A Red Fir 10" dia., bears S.35°E., 54 lks. dist.
A B.Oak 12" dia., bears N.38°W., 63 lks. dist.

Arthur R. Evans, Deputy Co. Surveyor - Wit: F.D. Smith; Harvey Potter; Ivan Taylor - May 1949 - C.S. File 43/94 and M 1-31; Vol. 5 Pg. 17

Set 1¼" I.P. for cor. blazed and scribed BTs:
14" Laurel N.46°E., 24.4 ft. mkd. T29S R4W ¼ S25 CS BT
14" Fir S.35°W., 11.3 ft. mkd. T29S R4W ¼S26 CS BT. Nailed brass disk to this tree, mkd. Co. Surv. Off. ¼ Cor. 25 26 set by Reg. Engr. Ore. No. 2741.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126126

Found - 1½" I.P. at corner.
NE BT is OK.
14" Fir S.35°W., 11.3 ft., now stump.
New BT - 9" Fir S.14°W., 14.9 ft. scribed ¼ S26 CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15859)

The ¼ sec. cor., reestablished by proportionate measurement by Evans in 1949, monumented with an iron pipe, 1¼" dia., firmly set, projecting 6" above ground. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, from which the remains of bearing trees mkd. by Evans:

A Madrone 19" dia., bears N.41°E., 37 lks. dist, with scribe marks 29 R4W ¼ S25 CS BT visible on partially healed blaze.

A sawed Fir stump 18" dia., bears S.30½°W., 17 lks. dist., with scribe marks T29S ¼ S35 CS BT visible on partially healed blaze.

and a bearing tree mkd. by Byron in 1963:

A Fir 12" dia., bears S.16°W., 22 lks. dist. with illegible scribe marks visible on partially healed blaze.

(Cont. Next Page)

