

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6362-63)

Set a post cor. of secs. 23, 24, 25 and 26, from which
A Red Fir 18" dia., bears S.28°W., 45 lks. dist.
A Red Fir 12" dia., bears S.68°W., 33 lks. dist.
A B.Oak 10" dia., bears N.39°E., 49 lks. dist.
A Laurel 14" dia., bears N.49°W., 62 lks. dist.

F. C. Frear, Deputy Co. Surveyor - Wit: Jesse Smith; Ralph Smith; Jeff Wiley - June/July 1918 -C.S. File 6/23; C.S. File 6/6; M 1-33 (Cody & Black Survey) (and "old" cor. bk Pg. 122)

Reestablished from intersecting line.
Set in 1½" x 40" Iron pipe and a 5" Cedar post, from which
A Cedar 8" dia., bears N.46°40'E., 32½ lks.
A Cedar 24" dia., bears S.47°00'E., 24 lks.
A Cedar 24" dia., bears S.63°00'W., 9 lks.
A Fir 40" dia., bears N.36°15'W., 25 lks.
No old BTs found.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. Stoffel crew - April 1963 - C.S. File 52/126-126

Found - 1¼" I.P. at corner.
NW and SW BTs now down.
New BT - 38" Laurel N.19°W., 51.0 ft. scribed S23 T29S R4W CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15860)

The sec. cor., reestablished by proportionate measurement by Germond and Frear in 1918, monumented with an iron pipe 1¼" dia., firmly set, projecting 2" above ground. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, from which the remains of bearing trees mkd. by Germond and Frear:

- A Cedar 16" dia., bears N.46 3/4°E., 32½ lks. dist. with healed blaze.
- A Cedar 27" dia., bears S.47°E., 24 lks. dist. with healed blaze.
- A root hole bears S.63°W., 9 lks. dist. with a down Cedar alongside, 25" dia., with healed blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A root hole bears N.36¼°W., 25 lks. dist. with a down Fir alongside 43" dia., with healed blaze. and a bearing tree mkd. by Byron in 1963:

A Madrone 39" dia., bears N.19°W., 77 lks. dist. with scribe marks T29S R4W S23 CS BT visible on partially healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron pipe, with brass cap mkd:

T 29	S R 4	W
S 23		S 24
S 26		S 25
1967		

from which a new bearing tree

A Cedar 10" dia., bears S.44°W., 147½ lks. dist. mkd. T29S R4W S26 BT.

Fd. OK, Jan. 1995 by R. Brown - M 121-36