

PRIMARY CORNER DESCRIPTION Sec cor for 13, 14, 23 and 24

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 - (DCSO records Vol. 15 Page(s) 6364)  
-----  
Set a post cor. of secs. 13, 14, 23 and 24, from which  
A B.Oak 20" dia., bears N.10°E., 5 lks. dist.  
A B.Oak 10" dia., bears N.76°W., 54 lks. dist.  
A W.Oak 12" dia., bears S.74°W., 47 lks. dist.  
A W.Oak 10" dia., bears S.80°E., 700 lks. dist.

F.C. Frear, Deputy Co. Surveyor - Wit: Jesse Smith; Ralph Smith; Jeff Wiley - June/July 1918 - C.S. File 6/23; C.S. File 6/6; M 1-33 (and "old" corner book, page 122)  
-----  
Set in from old BTs, a 2" x 36" Iron pipe, from which  
A 36" B.Oak bears N.25°00'E., .05 lks.  
An 18" B.Oak bears N.76°00'W., 54 lks.  
A 30" W.Oak bears S.54°30'W., 57 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Mike Darby; Wm. S. Stoffel crew - March 1963- C.S. File 52/126-98  
-----  
Found - 2" I.P. at corner.  
NW and SW BTs OK. NE BT, now down.  
New BT - 4" Laurel bears N.57°E., 17.9 ft. scribed S13 CS BT.

BLM Resurvey by James E. Jelley and Lynn Roseberry Cadastral Surveyors under Group #'s 255; 701; 938 - Surveyed July 1967/Oct 1977 (DCSO records Vol. 39 Page(s) 15864-65)  
-----  
The Sec. cor., perpetuated and recorded by Germond and Frear, in 1918, monumented with an iron pipe, 2" dia., firmly set, projecting 5" above ground, from which the remains of the original bearing trees:  
A B.Oak stump 36" dia., bears N.25°E., 5 lks. dist., no marks visible. (Record, N.10°E.)  
A W.Oak 50" dia., bears S.54½°W., 59½ lks. dist. with healed blaze. (Record, S.74°W., 47 lks.)  
A B.Oak 25" dia., bears N.74½°W., 54 lks. dist., with healed blaze. (Record N.76°W.)  
and a bearing tree mkd. by Byron in 1962  
A Madrone 6" dia., bears N.59¼°E., 27 lks. dist., with scribe marks S13 CS BT visible on partially healed blaze.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
(Cont. Next Page)

TOWNSHIP 29 RANGE 04 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

T 29 S R 4 W  
S 14 | S 13  
S 23 | S 24  
1964

No suitable trees available within limits in sec. 24.  
Reset iron pipe alongside iron post.  
Corner is located at the cor. of wire fences extending E.,  
S., and W.

BLM dependent resurvey by Bryan S. Seibold, Cadastral  
Surveyor & Robert H. Browning, Surveying Technician, under  
Group #1775, surveyed Aug./Sept.. 1995 - (DCSO records Vol.  
52 Page(s) 19941)

-----  
Beginning at the cor. of secs. 13, 14, 23, & 24, perpetuated  
by Frear, in 1918, further perpetuated by Byron, Deputy  
County Surveyor, in 1962; monumented with an iron post, 2½"  
diam., firmly set, projecting 8" above ground (alongside of  
which is an inverted iron post, 2½" diam., firmly set,  
projecting 5" above ground), with brass cap mkd.

T29S R4W  
S 14 | S 13  
S 23 | S 24  
1967

from which the remains of an original bearing tree  
An oak snag, size indeterminate, bears N.74½°W., 54 lks.,  
no marks visible.  
and the remains of a bearing tree mkd. by Byron  
A madrone stump, size indeterminate, bears N.59¼°E., 27  
lks. no marks visible.  
and new bearing trees  
A pine, 6" diam., bears N.1¼°E., 123 lks., mkd. X BT.  
A madrone, 5" diam., bears N.56½°E., 27 lks., mkd. X BT.  
A madrone, 6" diam., bears S.33°E., 81 lks., mkd. T29S R4W  
S24 BT.

No suitable trees within limits to the SW.

Fd. BLM BC & BTs as per rec. by D Saily, 12/2023 - M183-28